



O-Crystal / SERIES
Outdoor transparent
Led Screen

 **STREET CO'**
DISPLAY SOLUTION EXPERT
www.streetcommunication.com



Parameters

SPECIFICATION				
Pixel Pitch	3.9–7.8mm	5.2–10.4mm	10.4mm	15.6mm
Encapsulation brand	NationStar			
LED lamp bead model	SMD1912	SMD1921	SMD2727	SMD2727
Pixel composition	1R1G1B			
Module Reslution(W*H)	128x32 dot	96x24 dot	48x24 dot	32x16 dot
Module Size(W*H)	500x250mm			
Module Fixed Way	Front & Real Access (Screw)			
Panel Reslution(W*H)	256x64 dot	192x48 dot	96x48 dot	64x32 dot
Panel Size(W*H*D)	1000x500mm			
Module Arrangement(W*H)	2x2			
Panel Weight (kg/sqm)	15kg			
Panel Material	Aluminum Die-casting			
Flatness between modules	≤0.1mm			
Maintenance Way	Rear Access			
Density of Pixel (dots/m2)	32768	18432	9216	4096
Brightness(cd/m2)	4500	4500	4500	6500
Viewing angle	140°/140°			
Transparency rate	55%	58%	58%	72%
Contrast	6000:1			
Protection level	Ip65			
Gray scale	14bit			
Chromaticity uniformity	±0.003 within Cx,Cy			
Scan mode	1/8	1/4	1/2	Static
Frame change frequency	60			
Refresh rate	<3840			
Color temperature	2000K~9500K			
Operating platform	Windows XP /7/8/10			
Signal Input	HDMI、DVI			
Operating Voltage	AC: 110V~240V、50~60Hz			
Maximum Power (W/m2)	800			
Average power (W/m2)	240			
Continuous working time	≥7x24hrs			
Service life	100000Hours			
Operating environment	0℃~40℃ 35%~85%RH			