



STREET CO'

DISPLAY SOLUTION EXPERT

www.streetcommunication.com



CE FC CCC RoHS

www.muxwave.com

Application



Specifications

Model	A3-2	A3-4
Pixel Pitch (mm)(horizontal / vertical)	P3.91 / P3.91	P3.91 / P3.91
Pixel Density(dot/m ²)	65536	65536
Transparency Rate	80%	80%
Display Dimension (mm) (w*h)	1000x2000	2000x2000
Profile Dimension (mm) (w*h)	1020x2230x75/1020x2452x500	2020x2230x75/2020x2452x500
Resolution (dot) (w*h)	256x512	512x512
Brightness(cd/m ²)	≥4000	≥4000
Weight(Kg/m ²)	40	60
Encapsulation Type	Light Board & Driving Board Integrated	Light Board & Driving Board Integrated
Scanning Mode	Static Driving (Single Pixel Single Control)	Static Driving (Single Pixel Single Control)
Lifespan	≥100,000.00 hours	≥100,000.00 hours
Pixel Configuration	16bit	16bit
Maximum Power Consumption (w/m ²)	1200	1200
Average Power Consumption (w/m ²)	500	500
Control System	Colorlight / Novastar	Colorlight / Novastar
Input Voltage	AC100~240V 50/60 Hz	AC100~240V 50/60 Hz
Working Voltage for Module	DC 4.2V ± 0.2V	DC 4.2V ± 0.2V
Working Temperature	Temperature 0°C~50°C	Temperature 0°C~50°C
Working Humidity	Humidity: 20% -85% (Without Condensation)	Humidity: 20% -85% (Without Condensation)
Storage Temperature	Temperature -20°C~60°C	Temperature -20°C~60°C
Storage Humidity	Humidity: 10% -85% (Without Condensation)	Humidity: 10% -85% (Without Condensation)
Protection Degree	IP20	IP20
Frame Material	Aviation Aluminum Alloy	Aviation Aluminum Alloy
Installation Environment	Indoor	Indoor
Installation Way	Pearl Cotton+Wooden case/Airbox	Pearl Cotton+Wooden case/Airbox

Statement: The relevant parameters in the table are subject to real-time update, and the data is for reference only. Upgrade will be made without further notice.