



STREET CO'

DISPLAY SOLUTION EXPERT

www.streetcommunication.com



Specifications

Model	M3	M6
Pixel Pitch (mm)(horizontal / vertical)	P3.91/P3.91	P6.25/P6.25
Pixel Density(dot/m ²)	65536	25600
Transparency Rate	80%	90%
Display Dimension (mm) (w*h)	250x1000/250x1200	250x1200/250x1500
Resolution (dot) (w*h)	64x256/64x300	40x188/40x236
Brightness(cd/m ²)	≥4000	≥5000
Weight(Kg/m ²)	6	5
Encapsulation Type	Light Board & Driving Board Integrated	Light Board & Driving Board Integrated
Scanning Mode	Static Driving (Single Pixel Single Control)	Static Driving (Single Pixel Single Control)
Lifespan	≥100,000.00 hours	≥100,000.00 hours
Pixel Configuration	16bit	16bit
Maximum Power Consumption (w/m ²)	1200	1200
Average Power Consumption (w/m ²)	500	500
Control System	Colorlight / Novastar	Colorlight / Novastar
Input Voltage	AC100~240V 50/60 Hz	AC100~240V 50/60 Hz
Working Voltage for Module	DC 4.2V ± 0.2V	DC 4.2V ± 0.2V
Working Temperature	Temperature 0°C~50°C	Temperature 0°C~50°C
Working Humidity	Humidity: 20% -85% (Without Condensation)	Humidity: 20% -85% (Without Condensation)
Storage Temperature	Temperature -20°C~60°C	Temperature -20°C~60°C
Storage Humidity	Humidity: 10% -85% (Without Condensation)	Humidity: 10% -85% (Without Condensation)
Protection Degree	IP20	IP20
Frame Material	Aviation Aluminum Alloy	Aviation Aluminum Alloy
Installation Environment	Indoor	Indoor
Installation Way	Pearl Cotton+Wooden case/Airbox	Pearl Cotton+Wooden case/Airbox

Statement: The relevant parameters in the table are subject to real-time update, and the data is for reference only.
Upgrade will be made without further notice.