

Product Evaluation Report

Rule 61G20-3 F.A.C. | Report No. 1955, Rev. 4 | Project No. 423-0605 | 8/15/23 | Page 1 of 2

Product Manufacturer

Elixir Door and Metal Company
1215 Pope Drive
Douglas, GA 31533

Product Name, Model and/or Description

Non-Impact Glazed, Inswing, Vinyl Laminated Steel
Door with Storm Door – X

Code: Current Edition of the Florida Building Code including the 8th Edition (2023) Florida Building Code

Compliance Method: 61G20-3.005(1)(a) – Certification Mark or Listing

Product Testing, Materials and Certification: Test Reports by Construction Consulting Laboratory

- ELIX0060: # CCL-19-196, dated November 5, 2019 to ASTM E330-14

Product Installation Instructions:

- ELIX0060, Rev. B: Model 7500 Non-Impact Inswing Vinyl Laminated Steel Door w/Storm Door

Engineering Analysis & Evaluation: Anchorage to structural substrate has been verified by calculation (PTC PDG Calc. No. 1936, Rev. 0) prepared, signed and sealed by Robert J. Amoruso, P.E. in accordance with the current edition of the Florida Building Code.

Limitations & Conditions of Use:

- This product has NOT been evaluated for use inside the HVHZ (High Velocity Hurricane Zone).
- This product will require an impact protection device in wind-borne debris region.
- Refer to Product Installation Instructions noted above for:
 - Maximum allowable wind loads at related maximum allowable size(s).
 - Overall dimensions and material/grade of main product components, accessories, etc.
 - Illustrated diagrams of the attachment of the product to substrate structure.
 - Anchor type(s), size(s), substrate(s), embedment, edge distance, and spacing/locations.
- Site wind pressures shall be determined by a licensed professional engineer in accordance with the current edition of the Florida Building Code (and/or ASCE 7 as referenced in the current edition of the Florida Building Code) for components and cladding based on allowable stress design.
- Site conditions not covered in this product evaluation document are subject to additional engineering analysis by a licensed professional engineer or registered architect as required by the authority having jurisdiction.
- Adequacy of the existing structural substrates as a main wind force resisting system capable of withstanding and transferring applied product loads to the foundation is the responsibility of the licensed professional engineer or registered architect acting as the design professional of record for the project of installation.



Product Evaluation Report

Rule 61G20-3 F.A.C. | Report No. 1955, Rev. 4 | Project No. 423-0605 | 8/15/23 | Page 2 of 2

Certificate of Independence per Product Approval Rule 61G20-3.009

PTC Product Design Group, LLC and Robert J. Amoruso, P.E. does not have, nor will acquire, any financial interest in the company manufacturing or distributing product(s) covered by this Product Evaluation Report.

PTC Product Design Group, LLC and Robert J. Amoruso, P.E. do not have, nor will acquire any financial interest in any other entity involved in the approval process or testing of the product(s) covered by this Product Evaluation Report.

Evaluated By:

Robert J. Amoruso, P.E.
FL P.E. License Number 49752

