

5.2K EAGLE DUMP



STANDARD FEATURES

- 2 5/16" Coupler w/ 2K Top Wind Tongue Jack
- Brakes on Axle
- PPG Primer & Paint
- Tube Tongue (Longer than competition)
- Stake Pockets
- Front and Rear Diamond Plate Fender Steps
- 2" Flat Bar Heavy Duty Tie Rail
- Trickle Charge Line From Tow Vehicle
- 15" Wheels & Tires (Radial)
- Direct Push 5" Bore Hydraulic Cylinder
- Sealed Beam LED Lights
- Electric/Hydraulic Pump with Reservoir and Gravity Override
- Tarp Bar
- Lockable Tongue Box
- GPS Tracker

POPULAR OPTIONS


- Stored Heavy Duty Ramps w/ 4 D-Rings
- Spare Tire and Mount
- Dual Action Spreader Gate
- Metal Cover Mesh Roll Tarp System
- Scissor Lift ILO 5" Direct Push Cylinder
- Higher Sides - 31" or 43"
- Fold Down and/or Removable Higher Sides
- Side Foot Step
- 110 Volt Charger
- Extensions - 24"

| MODEL | DESCRIPTION | GVWR | CURB WEIGHT |
|----------|--------------------------------------|-------|-------------|
| ED508SA3 | 5' x 8' 5.2K Eagle Single Axle Dump | 5,200 | 1,540 |
| ED510SA3 | 5' x 10' 5.2K Eagle Single Axle Dump | 5,200 | 1,625 |
| ED610SA3 | 6' x 10' 5.2K Eagle Single Axle Dump | 5,200 | 1,690 |


5.2K EAGLE DUMP TRAILER SPEC SHEET

| STANDARD SPECIFICATIONS | | | |
|-------------------------|--|-----------------------|---|
| GVWR | 5,200# | GAWR | 5,200# |
| Main Frame | 4" Channel 3" Channel Cross Members & Reinforced Frame for Direct Push 5" Bore Hydraulic Cylinder | Dump Box Frame | 2" x 4" Rectangle Tube (.120") 1 ½" x 1 ½" Heavy Wall Tubing 16" on Center Barn Doors 10 gauge sides (Note: with ramps 2" x 5" dump box frame) |
| Axle | 5,200# Posi-Lube Axle with Brakes | Fenders | 10" x 32" |
| Coupler | 2 5/16" Coupler | Suspension | Multi-Leaf Spring |
| Hoist | Electric/Hydraulic Direct Push Cylinder Hoist (45° dump angle or more) Greaseable Zerk | Ramps | Optional |
| Coupler Height | 18" | Uprights | 2" x 4" Rectangle Tube |
| Deck Height | 25" | Sides | 10 gauge |
| Tongue | 2" x 4" Rectangle Tube | Lights | Sealed Beam LED D.O.T |
| Jack | 2K Top Wind | Decking | 10 gauge Steel Floor |
| Safety Chain | 30" x 5/16" 5.2K Capacity | Electric Plug | 7-Way RV Molded Water Tight Plug |
| Tires | ST 225/75 R15 Load Range D | Wheels | 15 x 6 6-5.5 Mod (Silver) |
| Finish | Steel is cleaned (wiped down) to ensure quality protective finish | Paint | PPG Primer and Paint |

STANDARD COLORS



Black ALK-FP901



Eagle Majestic Grey

OPTIONAL COLORS



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK - FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701