

### STANDARD FEATURES

- Adjustable 2 5/16" Coupler w/ 12K Drop Leg Jack
- Stake Pockets
- Tube Tongue (Longer than competition)
- Trickle Charge Line From Tow Vehicle
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- Electric/Hydraulic Pump with Reservoir and Gravity Override
- PPG Primer and Paint

- Lockable Tongue Box
- Heavy Duty Ramps 6'
- Spare Tire Mount
- Front and Rear Diamond Plate Fender Steps
- 4 D Rings
- Tarp Bar
- · Heavy Duty Diamond Plate Fenders
- 3/16" Floor and 10 gauge Sidewalls
- GPS Tracker

### **POPULAR OPTIONS**

- Spare Tire
- Dual Action Spreader Gate
- Metal Cover Mesh Roll Tarp System

- Higher Sides 31", 43" or 55"
- 110 Volt Charger
- 14 ply Tire

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
BHD710TA5	7' x 10' Blackhawk Tandem Axle Dump	14,000	3,180
BHD712TA5	7' x 12' Blackhawk Tandem Axle Dump	14,000	3,385
BHD714TA5	7' x 14' Blackhawk Tandem Axle Dump	14,000	3,600
BHD716TA5	7' x 16' Blackhawk Tandem Axle Dump	14,000	3,910

# 14K / 16K BLACKHAWK DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	14,000#	GAWR	14,000#		
Main Frame	6" Channel 4" Channel Cross Members I-Beam Support (Scissor Lift)	Floor 3/16" Smooth Steel			
Axle	2 (7,000#) Posi-Lube Axle with Brakes				
Coupler	2 5/16" Adjustable Coupler	Fenders	10" x 72" Diamond Plate Jeep Style		
Hoist	Electric/Hydraulic Direct Push Cylinder Hoist (45° dump angle or more) Greasable Zerks	Suspension	Multi-Leaf Spring		
Coupler Height	Adjustable	Ramps	3" Channel Heavy Duty 6' Ramps		
Deck Height	30"	Uprights 4" x 2" x 0.120" Rectangle Tube			
Tongue	2" x 6" Rectangle Tube (.120 thick wall)	Top Rail	10 gauge Formed		
lack	10K Drop Leg	Lights	Sealed Beam LED D.O.T		
Safety Chain	36" x 3/8" 16.2K Capacity	Decking	10 gauge Steel Floor		
Tires	ST 235/80 R16 Load Range E	Electric Plug	7-Way RV Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Wheels	16 x 6 8-6.5 Mod (Black)		
		Paint	PPG Primer and Paint		

# **STANDARD COLORS**



## **OPTIONAL COLORS**

