

# 7K EAGLE DUMP



## STANDARD FEATURES

- 2 5/16" Coupler w/ 2K Top Wind Tongue Jack
- Brakes on Both Axles
- 10 gauge Floor and Sidewalls
- Tread Plate Fenders
- Stake Pockets
- Tube Tongue (Longer than competition)
- Front and Rear Diamond Plate Fender Steps
- 2" Flat Bar Heavy Duty Tie Rail
- Trickle Charge Line From Tow Vehicle
- HD Deep Cycle Battery
- 15" Wheels & Tires (Radial)
- Direct Push 5" Bore Hydraulic Cylinder
- Sealed Beam LED Lights
- Electric/Hydraulic Pump with Reservoir and Gravity Override
- PPG Primer and Paint
- Tarp Bar
- Lockable Tongue Box
- GPS Tracker

## POPULAR OPTIONS

- Stored Heavy Duty Ramps w/ 4 D-Rings
- Spare Tire and Mount
- Dual Action Spreader Gate
- Metal Cover Mesh Roll Tarp System
- Scissor Lift ILO Direct Push Cylinder
- Higher Sides
- 110 Volt Charger

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
ED508TA2	5' x 8' 7K Eagle Tandem Axle Dump	7,000	2,110
ED510TA2	5' x 10' 7K Eagle Tandem Axle Dump	7,000	2,200
ED610TA2	6' x 10' 7K Eagle Tandem Axle Dump	7,000	2,270
ED612TA2	6' x 12' 7K Eagle Tandem Axle Dump	7,000	2,440
ED710TA2	7' x 10' 7K Eagle Tandem Axle Dump	7,000	2,400
ED712TA2	7' x 12' 7K Eagle Tandem Axle Dump	7,000	2,580


# 7K EAGLE DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS			
GVWR	7,000#	GAWR	7,000#
Main Frame	4" Channel 3" Channel Cross Members & Reinforced Frame for Direct Push 5" Bore Hydraulic Cylinder	Dump Box Frame	2" x 4" Rectangle Tube (.120") 1 ½" x 1 ½" Heavy Wall Tubing 16" on Center Barn Doors 10 gauge sides (Note: with ramps 2" x 5" dump box frame)
Axle	7,000#	Fenders	9" x 72" Diamond Plate Double Broke
Coupler	2 5/16" Coupler	Suspension	Multi-Leaf Spring
Hoist	Electric/Hydraulic Direct Push Cylinder Hoist (45° dump angle or more) Greaseable Zerk	Ramps	Optional
Coupler Height	18"	Uprights	2" x 4" Rectangle Tube
Deck Height	28"	Sides	10 gauge
Tongue	2" x 4" Rectangle Tube (.120 thick wall)	Lights	Sealed Beam LED D.O.T
Jack	2K Top Wind	Decking	10 gauge Steel Floor
Safety Chain	30" x 5/16" 7.6K Capacity	Electric Plug	7-Way RV Molded Water Tight Plug
Tires	ST 205/75 R15 Load Range C	Wheels	15 x 5 5-4.5 Mod (Silver)
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint

## STANDARD COLORS



Black ALK-FP901



Eagle Majestic Grey

## OPTIONAL COLORS



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK - FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701