

16K RAPTOR LOW PRO DUMP



STANDARD FEATURES

- 8" iBeam Tongue and Frame Construction
- Trickle Charge Line From Tow Vehicle
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D - Rings
- Heavy Duty Diamond Plate Fenders
- 10 Gauge 24" or 48" Sidewalls
- 3" x 3/16" Channel Cross Members
- 4" Full Length Bed Runners and Ramp Pockets
- Metal Cover Mesh Tarp Roll System
- 110 Volt Charger
- Drop Down Rear Stabilizer Jacks
- Front Frame Tool Step
- Expanded Metal Tool Tray Under Dump Box
- Electric Over Hydraulic Pump and Reservoir with Gravity Override
- Tarp Bar
- Dual Action Spreader Gate

POPULAR OPTIONS

- Spare Tire
- 24" Expanded Metal Mesh Side Extensions
- Solar Charger (1.5 Amp)
- Gooseneck Option
- Two 10K Axel Upgrade (20K Rated)

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
RDL24714TA6	7' x 14' 16K Raptor Tandem Axle Dump, 24" Sides	16,000	4,050
RDL36714TA6	7' x 14' 16K Raptor Tandem Axle Dump, 36" Sides	16,000	4,275
RDL48714TA6	7' x 14' 16K Raptor Tandem Axle Dump, 48" Sides	16,000	4,370
RDL24716TA6	7' x 16' 16K Raptor Tandem Axle Dump, 24" Sides	16,000	4,150
RDL36716TA6	7' x 16' 16K Raptor Tandem Axle Dump, 36" Sides	16,000	4,410
RDL48716TA6	7' x 16' 16K Raptor Tandem Axle Dump, 48" Sides	16,000	4,550


16K RAPTOR LOW PRO DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS			
GVWR	16,000#	GAWR	16,000#
Main Frame	8" iBeam Frame	Dump Box	3" x 3/16" Channel Cross Members 2" x 6" Rectangle Tube (.120") 5" Channel Full Length Runners 8 gauge Floors, 10 gauge Sidewalls Three-Way Spreader Gate
Axle	8,000# Axles with Brakes	Fenders	10" x 72" Jeep Style Double Broke Diamond Plate Walk on Fenders
Coupler	2 5/16"	Suspension	Multi-Leaf Spring
Hoist	Electric/Hydraulic Scissor Hoist, Power up/Power Down Control with Gravity Override (45° dump angle or more) Greaseable Zerks	Ramps	7' HD Ramps 3" Channel with Lockable Door
Coupler Height	13.5" to 21.5"	Uprights	2" x 6" Rectangle Tube
Deck Height	33"	Top Rail	N/A
Tongue	HD 8" iBeam Low Pro	Lights	Sealed Beam LED D.O.T
Jack	12K Spring Loaded Drop Leg	Decking	8 gauge Steel Floor
Safety Chain	36" x 3/8" 16.2K Capacity	Electric Plug	7-Way RV Molded Water Tight Plug
Tires	ST 235/85 R16 Load Range G	Wheels	16 x 6 6-5.5 Mod (Black)
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint

STANDARD COLORS



Black ALK-FP901



Eagle Majestic Grey

OPTIONAL COLORS



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK - FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701