

#### STANDARD FEATURES

- 8" iBeam Tongue and Frame Construction
- Trickle Charge Line from Tow Vehicle
- 16" Wheels and Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- Spare Tire Mount
- 4 D Rings
- Heavy Duty Diamond Plate Fenders
- 10 gauge 24", 36" or 48" Walls, 8 gauge Floors
- 3" x 3/16" Channel Cross Members
- 4" Full Length Bed Runners and Ramp Pockets

- Stored HD Ramp
- Metal Cover Mesh Tarp Roll System
- 110 Volt Charger
- Electric/Hydraulic Pump and Reservoir with Gravity Override
- Rear Stabilizer Jacks
- Tarp Bar
- Expanded Metal Tool Tray Under Dump Box
- Front Frame Foot Step
- Dual Action Spreader Gate
- GPS Tracker

### **POPULAR OPTIONS**

- Spare Tire
- Two 8K Axle Upgrade (16K Rated)
- Two 10K Axle Upgrade (20K Rated)
- Three 7K Axle Upgrade (21K Rated)


- 24" Expanded Metal Mesh or Solid Side Extensions
- Gooseneck Option

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
RDL24714TA5	7' x 14' 14K Raptor Tandem Axle Dump, 24" Sides	14,000	3,790
RDL36714TA5	7' x 14' 14K Raptor Tandem Axle Dump, 36" Sides	14,000	4,015
RDL48714TA5	7' x 14' 14K Raptor Tandem Axle Dump, 48" Sides	14,000	4,110
RDL24716TA5	7' x 16' 14K Raptor Tandem Axle Dump, 24" Sides	14,000	3,890
RDL36716TA5	7' x 16' 14K Raptor Tandem Axle Dump, 36" Sides	14,000	4,150
RDL48716TA5	7' x 16' 14K Raptor Tandem Axle Dump, 48" Sides	14,000	4,290

# 14K RAPTOR LOW PRO DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	14,000#	GAWR	14,000#		
Main Frame	8" iBeam Frame	Dump Box	3" x 3/16" Channel Cross Members 2" x 6" Rectangle Tube (.120") 5" Channel Full Length Runners 8 gauge Floors, 10 gauge Sidewalls Three-Way Spreader Gate		
Axle	(2) 7,000# Axles with Brakes		10" x 72" Jeep Style		
Coupler	2 5/16" Adjustable Coupler	Fenders	Double Broke Diamond Plate Walk on Fenders		
	Electric/Hydraulic Scissor Hoist, Power up/Power Down Control with Gravity	Suspension	Multi-Leaf Spring		
Hoist	Override (45° dump angle or more) Greaseable Zerks	Ramps	7' HD Ramps 3" Channel with Lockable Door		
Coupler Height	13.5" to 21.5"	Uprights	2" x 6" Rectangle Tube		
Deck Height	33"	Top Rail	N/A		
Tongue	HD 8" iBeam Low Pro	Lights	Sealed Beam LED D.O.T		
Jack	12K Spring Loaded Drop Leg	Decking	8 gauge Steel Floor		
Safety Chain	36" x 3/8" 16.2K Capacity	Electric Plug	7-Way RV Molded Water Tight Plug		
Tires	ST 235/85 R16 Load Range E	Wheels	16 x 6 8-6.5 Mod (Black)		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

## **STANDARD COLORS**



### **OPTIONAL COLORS**

