# **7K / 10K EAGLE EQUIPMENT TILT**



#### STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D-Rings
- 2" x 6" #2 or Better Fir Decking

- Tube Tongue (longer than competition)
- 7K Drop Leg Jack
- Brakes on Both Axles
- 5' Steel Rear Full Approach Plate
- Heavy Duty Diamond Plate Fenders
- Frame Inside of Frame Construction

#### **POPULAR OPTIONS**


- Pressure Treated Decking
- Tongue Box Steel or Aluminum Diamond Plate
- Spare Tire and/or Mount (rear mounting)
- Cushioning Hydraulic Cylinder with Lock out Valve
- Cushioning Hydraulic Cylinder
- Tower Winch Mount/Bump Rail Mount
- Steel Decking Diamond Plate/Smooth/Sand Texture

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
EETB714TA2	7' x 14' Eagle Tandem Axle Equipment Tilt	7,000	2,480
EETB716TA2	7' x 16' Eagle Tandem Axle Equipment Tilt	7,000	2,590
EETB714TA3	7' x 14' Eagle Tandem Axle Equipment Tilt	10,000	2,840
EETB716TA3	7' x 16' Eagle Tandem Axle Equipment Tilt	10,000	3,090

## 7K / 10K EAGLE EQUIP TILT BED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	7,000# / 9,990#	GAWR	7,000# / 10,400#		
Frame	2" x 5" Tube	Cross Members	3" Channel		
Axle	(2) 5,200# Posi-Lube, 4" Drop Axle with Brakes (4" Drop)	Cross Members			
Coupler	Adjustable 2 5/16" Coupler	Fenders	10" x 72" Diamond Plate		
Coupler Height	Adjustable				
Deck Height	18"	Suspension	Multi-Leaf Spring		
Tongue	2" x 5" Rectangular Tube	Ramps	Full Width Rear Approach Plate		
Jack	7K Drop Leg Tongue	Uprights N/A			
Safety Chain	30" x 5/16" 7.6K Capacity	Bump Rail	2" x 2" Tube, 6" High		
Wheels	15 x 5 5 - 4.5 Mod (Silver) (7K)	Lights	Sealed Beam LED D.O.T		
	15 x 6 6 - 5.5 Mod (Silver) (10K) ST 205/75 R15 Load Range C (7K)	Decking	2 x 6 #2 or Better Fir Decking		
Tires	ST 225/75 R15 Load Range D (10K)	Electric Plug	7-Way RV Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

### **STANDARD COLORS**



### **OPTIONAL COLORS**

