

#### STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D-Rings
- Steel Deck
- Tube Tongue (longer than competition)

- 12K Drop Leg Tongue Jack
- Brakes on Both Axles
- Spare Tire Mount
- Heavy Duty Diamond Plate Fenders
- Cushioning Hydraulic Cylinder
- 30" Sloped Steel Rear Approach
- Non-Skid Sand Texture Surface

### **POPULAR OPTIONS**

- Tongue Box Steel or Aluminum Diamond Plate
- Cushioning Hydraulic Cylinder with Lock out Valve
- Tower Winch Mount/Bumper Mount
- Spare Tire

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
ВНРТ716ТА5	7' x 16' 14K Blackhawk Tandem Axle Pan Tilt	14,000	2,505
ВНРТ718ТА5	7' x 18' 14K Blackhawk Tandem Axle Pan Tilt	14,000	2,695
ВНРТ720ТА5	7' x 20' 14K Blackhawk Tandem Axle Pan Tilt	14,000	2,885

# 14K BLACKHAWK PAN TILT TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	14,000#	GAWR	14,000#		
Frame	6" x 3.5" x 5/16" Heavy Angle	Cross Members	3" Channel, 16" on Center		
Axle	(2) 7,000# Posi-Lube Axles with Brakes	Cross members			
Coupler	Adjustable 2 5/16" Coupler	Fenders	10" x 72" Diamond Plate Fender		
Coupler Height	Adjustable				
Deck Height	14"	Suspension	Multi-Leaf Spring		
Tongue	2" x 6" Rectangular Tube	Ramps	30" Steel Rear Approach		
Jack	12K Drop Leg	Uprights	N/A		
Safety Chain	36" x 3/8" 16.2K Capacity	Bump Rail	N/A		
Wheels	16 x 6 8 - 6.5 Mod (Black)	Lights	Sealed Beam LED D.O.T		
		Decking	3/16" Steel Floor		
Tires	ST 235/80 R16 Load Range E	Electric Plug	7-Way RV Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

## **STANDARD COLORS**



## **OPTIONAL COLORS**

