

### STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D-Rings
- 3/16" Smooth Plate Floor
- Tube Tongue (longer than competition)

- 5K Swing-up Tongue Jack with Pad
- Brakes on Axle
- Torsion Axle
- Heavy Duty Diamond Plate Fenders
- Cushioning Hydraulic Cylinder
- Over Center Latch with Release
- Non-Skid Sand Texture Surface

### **POPULAR OPTIONS**

- Tongue Box Steel or Aluminum Diamond Plate
- Cushioning Hydraulic Cylinder with Lock out Valve
- Tower Winch Mount/Front Mount
- · Diamond Plate Surface

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
EPT510SA3	5' x 10' 5K Eagle Single Axle Pan Tilt	5,200	1,215
EPT610SA3	6' x 10' 5K Eagle Single Axle Pan Tilt	5,200	1,295
EPT612SA3	6' x 12' 5K Eagle Single Axle Pan Tilt	5,200	1,365
EPT710SA3	7' x 10' 5K Eagle Single Axle Pan Tilt	5,200	1,415
EPT712SA3	7' x 12' 5K Eagle Single Axle Pan Tilt	5,200	1,485

# **5K EAGLE PAN TILT TRAILER SPEC SHEET**

STANDARD SPECIFICATIONS				
GVWR	5,000#	GAWR	5,200#	
Frame	5" x 3" Angle	Cross Members	3" Channel	
Axle	5,200# Torsion Axle with Brake	Cross Members		
Coupler	Adjustable 2 5/16" Coupler	Fenders	10" x 32" Diamond Plate	
Coupler Height	Adjustable			
Deck Height	13"	Suspension	Torsion	
Tongue	2" x 5" Rectangular Tube	Ramps	N/A	
Jack	5K Swing Up Tongue Jack with Pad	Uprights	N/A	
Safety Chain	36" x 5/16" 11.7K Capacity	Bump Rail	N/A	
Wheels	15 x 6 6 - 5.5 Mod (Silver)	Lights	Sealed Beam LED D.O.T	
		Decking	3/16" Steel Floor	
Tires	ST 225/75 R15 Load Range D	Electric Plug	7-Way RV Molded Water Tight Plug	
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint	

## **STANDARD COLORS**



### **OPTIONAL COLORS**

