

STANDARD FEATURES

- 2" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 3" Channel Frame
- Stake Pockets

- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)
- Front Bump Rail
- 4" Drop Axle
- Knife Edge Approach

POPULAR OPTIONS

- Swing up Tongue Jack with Wheel
- · Pressure Treated Decking
- Tongue Box Steel or Aluminum Diamond Plate
- Jeep Style Diamond Plate Fenders

- Hydraulic Damping Cylinder
- Adjustable 2 5/16" Coupler
- 4" Frame Upgrade with Damping Cylinder

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
ETB408SA	4' x 8' 3.5K Eagle Single Axle Tilt	2,990	775
ETB508SA	5' x 8' 3.5K Eagle Single Axle Tilt	2,990	820
ETB510SA	5' x 10' 3.5K Eagle Single Axle Tilt	2,990	880
ETB610SA	6' x 10' 3.5K Eagle Single Axle Tilt	2,990	930
ETB612SA	6' x 12' 3.5K Eagle Single Axle Tilt	2,990	990
ETB6610SA	6'6" x 10' 3.5K Eagle Single Axle Tilt	2,990	955
ETB6612SA	6'6" x 12' 3.5K Eagle Single Axle Tilt	2,990	1,015
ETB6614SA	6'6" x 14' 3.5K Eagle Single Axle Tilt	2,990	1,075
ETB712SA	7' x 12' 3.5K Eagle Single Axle Tilt	2,990	1,135
ETB714SA	7' x 14' 3.5K Eagle Single Axle Tilt (4" Frame)	2,990	1,235

3.5K EAGLE TILT TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	2,990#	GAWR	3,500#		
Frame	3" Channel	Cross Members	2" x 2" Angle		
Axle	3,500# Posi-Lube Axle, 4" Drop Axle	Fondone	011 2211		
Coupler	2" A-Frame	Fenders	9" x 32"		
Coupler Height	16"	Suspension	Multi-Leaf Spring		
Deck Height	19"	Ramps	N/A		
Tongue	2" x 3" Rectangle Tube	Uprights	N/A		
Jack	2K Top Wind Tongue	Bump Rail	1 1/2" x 1 1/2" Square Tube, 6" High		
Safety Chain	30" x 1/4" 5.2K Capacity	Lights	Sealed Beam LED D.O.T		
Wheels	15 x 5 5-4.5 Mod (Silver)	Decking	2 x 6 #2 or Better Fir Decking		
Tires	ST 205/75 R15 Load Range C	Electric Plug	4-Way Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

