10K RAPTOR LOW PRO DUMP





STANDARD FEATURES

- 6" iBeam Tongue and Frame Construction
- Trickle Charge Line From Tow Vehicle
- 15" Wheels and Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- Spare Tire Mount
- 4 D Rings
- Heavy Duty Diamond Plate Fenders
- Dual Action Spreader Gate
- Scissor Hoist

- 10 gauge 24", 36" or 48" Walls, 8 gauge Floors
- 3" x 3/16" Channel Cross Members
- Ramp Pockets
- Stored HD Ramp
- Metal Cover Mesh Tarp Roll System
- 110 Volt Charger
- Tarp Bar
- Electric/Hydraulic Pump and Reservoir with Gravity Override
- GPS Tracker

POPULAR OPTIONS

- Rear Stabilizer Jacks
- 24" Expanded Metal Mesh or Solid Side Extensions
- Pintle Eye
- Spare Tire

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
RDL24610TA3	6' x 10' 10K Raptor Tandem Axle Dump, 24" Sides	10,000	2,405
RDL36610TA3	6' x 10' 10K Raptor Tandem Axle Dump, 36" Sides	10,000	2,670
RDL48610TA3	6' x 10' 10K Raptor Tandem Axle Dump, 48" Sides	10,000	2,860
RDL24612TA3	6' x 12' 10K Raptor Tandem Axle Dump, 24" Sides	10,000	2,595
RDL36612TA3	6' x 12' 10K Raptor Tandem Axle Dump, 36" Sides	10,000	2,860
RDL48612TA3	6' x 12' 10K Raptor Tandem Axle Dump, 48" Sides	10,000	3,050
RDL24710TA3	7' x 10' 10K Raptor Tandem Axle Dump, 24" Sides	10,000	2,525
RDL36710TA3	7' x 10' 10K Raptor Tandem Axle Dump, 36" Sides	10,000	2,795
RDL48710TA3	7' x 10' 10K Raptor Tandem Axle Dump, 48" Sides	10,000	3,070
RDL24712TA3	7' x 12' 10K Raptor Tandem Axle Dump, 24" Sides	10,000	2,740
RDL36712TA3	7' x 12' 10K Raptor Tandem Axle Dump, 36" Sides	10,000	3,010
RDL48712TA3	7' x 12' 10K Raptor Tandem Axle Dump, 48" Sides	10,000	3,285

10K RAPTOR LOW PRO DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	10,000#	GAWR	10,400#		
Main Frame	6" Channel 3" Channel Cross Members	Dump Box	3" x 3/16" Channel Cross Members 2" x 5" Rectangle Tube (.120") 8 gauge Floors, 10 gauge Sidewalls Three-Way Spreader Gate		
Axle	(2) 5,200# Axles with Brakes	Fenders	9" x 72" Double Broke Diamond Plate		
Coupler	2 5/16" Adjustable Coupler	renders	Walk on Fenders		
	Electric/Hydraulic Scissor Hoist, Power up/Power Down Control with Gravity Override (45° dump angle or more) Greaseable Zerks Suspension Ramps	Suspension	Multi-Leaf Spring		
Hoist		Ramps	7' HD Ramps 3" Channel with Lockable Door		
Coupler Height	13.5" to 21.5"	Uprights	2" x 4" Rectangle Tube		
Deck Height	30"	Top Rail	N/A		
Tongue	HD 6" iBeam Low Pro	Lights	Sealed Beam LED D.O.T		
Jack	7K Drop Leg	Decking	8 gauge Steel Floor		
Safety Chain	36" x 5/16" 11.7K Capacity	Electric Plug	7-Way RV Molded Water Tight Plug		
Tires	ST 225/75 R15 Load Range D	Wheels	15 x 6 6-5.5 Mod (Silver)		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

