

STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- Stake Pockets & 4 D-Rings
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)

- 4" Drop Axles
- 5K Swing-up Tongue Jack with Pad
- 84" Between Fenders
- Brakes on Both Axles
- Full Width Rear Approach Plate
- Hydraulic Cushioning Cylinder
- Over Center Latch with Release

POPULAR OPTIONS

- Pressure Treated Decking
- Tongue Box Steel or Aluminum Diamond Plate
- 1/8" Steel Decking Diamond Plate or Smooth
- Removable Fenders

- Spare Tire and/or Mount (rear mounting)
- Cylinder Lock out Valve (so multiple pieces of equipment can be loaded)
- Tower Winch Mount/Bump Rail Mount

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
E4TB716TA2	7' x 16' 7K Eagle 4" Frame Tandem Axle Tilt Bed	7,000	1,740
E4TB718TA2	7' x 18' 7K Eagle 4" Frame Tandem Axle Tilt Bed	7,000	1,830
E4TB720TA2	7' x 20' 7K Eagle 4" Frame Tandem Axle Tilt Bed	7,000	1,920

7K EAGLE 4" FRAME TILT BED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	7,000#	GAWR	7,000#		
Frame	4" Channel	Cross Members	2" x 2" Angle		
Axle	(2) 3,500# 4" Drop Axle with Brakes	Fondous	011 6611		
Coupler	Adjustable 2 5/16" Coupler	Fenders	9" x 66"		
Coupler Height	Adjustable	Suspension	Multi-Leaf Spring		
Deck Height	18"	Ramps	Full Width Rear Approach Plate		
Tongue	4" Tube Tongue	Uprights	N/A		
Jack	5K Swing Up Tongue	Bump Rail	2" x 2" Tube, 6" High		
Safety Chain	30" x 5/16" 7.6K Capacity	Lights	Sealed Beam LED D.O.T		
Wheels	15 x 5 5 - 4.5 Mod (Silver)	Decking	2 x 6 #2 or Better Fir Decking		
Tires	ST 205/75 R15 Load Range C	Electric Plug	7-Way RV Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

