

STANDARD FEATURES

- Adjustable 2 5/16" Coupler w/ Swing-up Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 3" Channel Frame
- Stake Pockets
- 2" x 6" #2 or Better Fir Decking

- Tube Tongue (longer than competition)
- Front Bump Rail
- 4" Drop Axle
- Knife Edge Approach
- 4" Frame
- Hydraulic Damping Cylinder
- Jeep Style Fender

POPULAR OPTIONS

· Pressure Treated Decking

Tongue Box (Steel or Aluminum Diamond Plate)

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
ETB408SA3	4' x 8' 5.2K Eagle Single Axle Tilt	5,200	875
ETB508SA3	5' x 8' 5.2K Eagle Single Axle Tilt	5,200	920
ETB510SA3	5' x 10' 5.2K Eagle Single Axle Tilt	5,200	980
ETB610SA3	6' x 10' 5.2K Eagle Single Axle Tilt	5,200	1,070
ETB612SA3	6' x 12' 5.2K Eagle Single Axle Tilt	5,200	1,125
ETB6610SA3	6'6" x 10' 5.2K Eagle Single Axle Tilt	5,200	1,055
ETB6612SA3	6'6" x 12' 5.2K Eagle Single Axle Tilt	5,200	1,225
ETB6614SA3	6'6" x 14' 5.2K Eagle Single Axle Tilt	5,200	1,295
ETB712SA3	7' x 12' 5.2K Eagle Single Axle Tilt	5,200	1,275
ETB714SA3	7' x 14' 5.2K Eagle Single Axle Tilt (4" Frame)	5,200	1,310

5.2K EAGLE TILT TRAILER SPEC SHEET

STANDARD SPECIFICATIONS				
GVWR	5,200#	GAWR	5,200#	
Frame	3" Channel	Cross Members	2" x 2" Angle	
Axle	5,200# Posi-Lube Axle, 4" Drop Axle	Fenders	011 2211	
Coupler	Adjustable 2 5/16" Coupler	renders	9" x 32"	
Coupler Height	16"	Suspension	Multi-Leaf Spring	
Deck Height	19"	Ramps	N/A	
Tongue	2" x 3" Rectangle Tube	Uprights	N/A	
Jack	2K Pipemount Swing Up with Pad	Bump Rail	1 1/2" x 1 1/2" Square Tube, 6" High	
Safety Chain	30" x 5/16" 7.6K Capacity	Lights	Sealed Beam LED D.O.T	
Wheels	15 x 6 6-5.5 Mod (Silver)	Decking	2 x 6 #2 or Better Fir Decking	
Tires	ST 225/75 R15 Load Range D	Electric Plug	4-Way Molded Water Tight Plug	
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint	

STANDARD COLORS



OPTIONAL COLORS

