7K EAGLE 5" FRAME EQUIPMENT TILT BED



STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- Stake Pockets & 4 D-Rings
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)

- 4" Drop Axles
- 5K Swing-up Tongue Jack with Pad
- 83" Between Fenders
- Brakes on Both Axles
- Full Width Rear Approach Plate
- Hydraulic Cushioning Cylinder
- Over Center Latch with Release

POPULAR OPTIONS

- Pressure Treated Decking
- Tongue Box Steel or Aluminum Diamond Plate
- 1/8" Steel Decking Diamond Plate or Smooth
- Removable Fenders

- Spare Tire and/or Mount (rear mounting)
- Cylinder Lock out Valve (so multiple pieces of equipment can be loaded)
- Tower Winch Mount/Bump Rail Mount

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
ETB716TA2	7' x 16' 7K Eagle 5" Frame Tandem Axle Tilt Bed	7,000	1,990
ETB718TA2	7' x 18' 7K Eagle 5" Frame Tandem Axle Tilt Bed	7,000	2,125
ETB720TA2	7' x 20' 7K Eagle 5" Frame Tandem Axle Tilt Bed	7,000	2,325

7K EAGLE 5" FRAME TILT BED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS				
GVWR	7,000#	GAWR	7,000#	
Frame	5" Channel	Cross Members	3" Channel	
Axle	(2) 3,500# Posi-Lube, 4" Drop Axle with Brakes			
Coupler	Adjustable 2 5/16" Coupler	Fenders	9" x 66" HD Smooth Fenders	
Coupler Height	Adjustable	Suspension	Multi-Leaf Spring	
Deck Height	20"	Ramps	Full Width Rear Approach Plate	
Tongue	2" x 5" Rectangular Tube	Uprights	N/A	
Jack	5K Swing Up Tongue	Bump Rail	2" x 2" Tube, 6" High	
Safety Chain	36" x 5/16" 11.7K Capacity	Lights	Sealed Beam LED D.O.T	
Wheels	15 x 5 5 - 4.5 Mod (Silver)	Decking	2 x 6 #2 or Better Fir Decking	
Tires	ST 205/75 R15 Load Range C	Electric Plug	7-Way RV Molded Water Tight Plug	
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint	

STANDARD COLORS



OPTIONAL COLORS

