

3.5K / 5.2K FALCON LIGHT SPEED



STANDARD FEATURES

- 2" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)
- Front Fender Step with Light
- 24" Solid Metal Sides
- Square Tube Top Tie Rail 30" Total Height
- Split Rear Gate Loading Ramps

POPULAR OPTIONS


- Tongue Box Steel or Aluminum Diamond Plate
- Pressure Treated Decking
- Swing up Tongue Jack with Wheel
- Nylon Reinforced Vinyl Tarp Complete with Aluminum Cross Supports and Nylon Stretch Tie Rope
- Solid Metal Rear Swing Gate
- Spare Tire and/or Mount
- Rear Barn Doors
- No Gap Stake Pocket Top
- Four Small D-Rings

| MODEL | DESCRIPTION | GVWR | CURB WEIGHT |
|----------|---|-------|-------------|
| FLS406SA | 4' x 6' Falcon Single Axle Light Speed | 2,990 | 610 |
| FLS408SA | 4' x 8' Falcon Single Axle Light Speed | 2,990 | 675 |
| FLS508SA | 5' x 8' Falcon Single Axle Light Speed | 2,990 | 700 |
| FLS510SA | 5' x 10' Falcon Single Axle Light Speed | 2,990 | 750 |
| FLS610SA | 6' x 10' Falcon Single Axle Light Speed | 2,990 | 825 |
| FLS612SA | 6' x 12' Falcon Single Axle Light Speed | 2,990 | 945 |


3.5K / 5.2K FALCON LIGHT SPEED TRAILER SPEC SHEET

| STANDARD SPECIFICATIONS | | | |
|-------------------------|---|----------------------|---|
| GVWR | 2,990# | GAWR | 3,500# |
| Frame | 2" x 2" x 3/16" Angle | Cross Members | 2" x 2" x 1/8" Angle |
| Axle | 3,500# Posi-Lube Axles (Idler) | Fenders | 9" x 32" |
| Coupler | 2" A-Frame | Suspension | Multi-Leaf Spring |
| Coupler Height | 16" | Ramps | Split Ramp 11" Wide, 2" x 1" Tube |
| Deck Height | 18" | Uprights | 2" x 1" Rectangle Tube |
| Tongue | 2" x 3" Rectangular Tube | Bump Rail | 1 1/2" x 1 1/2" Square Tube |
| Jack | 2K Top Wind Tongue | Sidewalls | 24" 16 gauge Smooth Steel 30" to Top of Rail |
| Safety Chain | 27" x 1/4" 5.2K Capacity | Lights | Sealed Beam LED D.O.T |
| Wheels | 15 x 5 5 - 4.5 Mod (Silver) | Decking | 2" x 6" #2 or Better Fir Decking |
| Tires | ST 205/75 D15 Load Range C | Electric Plug | Flat 4-Way Molded Water Tight Plug |
| Finish | Steel is cleaned (wiped down) to ensure quality protective finish | Paint | PPG Primer and Paint |

STANDARD COLORS



Black ALK-FP901



Eagle Majestic Grey

OPTIONAL COLORS



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK - FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701