7K ANGLE FENDER HIGH RAIL FLATBED





STANDARD FEATURES

- 2 5/16" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- J-Hooks (4 per side, 1 in front)
- 2" x 6" #2 or Better Fir Decking

- Rectangle Tube Tongue (longer than competition)
- Brakes on Both Axles
- Stored Heavy Duty Ramps
- 84" Between Fenders
- · Fender High Square Tube Top Rail

POPULAR OPTIONS

- Tongue Box (Steel or Aluminum Diamond Plate)
- Pressure Treated Decking

- Spare Tire and/or Mount
- 4' Ramp Gate Straight or Bi-Fold ILO HD Ramps

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
FAFH714TA2	7' x 14' 7K Tandem Axle Angle Fender High Rail	7,000	1,560
FAFH716TA2	7' x 16' 7K Tandem Axle Angle Fender High Rail	7,000	1,695
FAFH718TA2	7' x 18' 7K Tandem Axle Angle Fender High Rail	7,000	1,790
FAFH720TA2	7' x 20' 7K Tandem Axle Angle Fender High Rail	7,000	1,895

7K ANGLE FENDER HIGH RAIL FB TRAILER SPEC SHEET

STANDARD SPECIFICATIONS				
GVWR	7,000#	GAWR	7,000#	
Frame	5" x 3" Angle	Cross Members	2" x 2" Angle	
Axle	(2) 3,500# Posi-Lube Axles with Brakes			
Coupler	2 5/16" Coupler	Fenders	84" Width Between Fenders 9" x 66" Fender	
Coupler Height	17"	Suspension	Multi-Leaf Spring	
Deck Height	19"	Ramps	5' Stored Heavy Duty	
Tongue	2" x 4" Rectangular Tube	Uprights	2" x 1" Tube	
Jack	2K Top Wind Tongue	Oprigiits		
Safety Chain	30" x 5/16" 7.6K Capacity	Bump Rail	1 1/2" x 1 1/2" Square Tube, Fender High	
Wheels	15 x 6 5 - 4.5 Mod (Silver)	Lights	Sealed Beam LED D.O.T	
		Decking	2" x 6" #2 or Better Fir Decking	
Tires	ST 205/75 D15 Load Range C	Electric Plug	7-Way Molded Water Tight Plug	
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint	

STANDARD COLORS



OPTIONAL COLORS

