14K / 16K BLACKHAWK DECKOVER



STANDARD FEATURES

- 2 5/16" Adjustable Coupler
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)

- 12K Drop Leg Tongue Jack
- Brakes on Both Axles
- 4 D-Rings
- 6' Heavy Duty Ramps
- Stake Pockets
- Heavy Duty Rub Rail

POPULAR OPTIONS


- Tongue Box Steel or Aluminum Diamond Plate
- · Pressure Treated Decking
- Spare Tire Mount/Spare Tire
- 1/8" Steel Decking Diamond Plate or Smooth
- Extended Rear Stabilizer Jacks
- Equipment Ramps with Support Elbows
- Flip up Heavy Duty Spring Assist Ramps
- Beavertail

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
BHDO8614TA5	8'6" x14' Blackhawk Tandem Axle Deckover	14,000	3,175
BHDO8616TA5	8'6" x 16' Blackhawk Tandem Axle Deckover	14,000	3,390
BHDO8618TA5	8'6" x 18' Blackhawk Tandem Axle Deckover	14,000	3,605
BHDO8620TA5	8'6" x 20' Blackhawk Tandem Axle Deckover	14,000	3,820
BHDO8622TA5	8'6" x 22' Blackhawk Tandem Axle Deckover	14,000	4,035
BHDO8624TA5	8'6" x 24' Blackhawk Tandem Axle Deckover	14,000	4,235

14K / 16K BLACKHAWK DECKOVER TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	14,000#	GAWR	14,000#		
Frame	5" Channel Upper Frame iBeam Heavy Wall Main Frame	Cross Members	3" Channel		
Axle	(2) 7,000# Posi-Lube Axle with Brakes				
Coupler	2 5/16" Adjustable	Fenders N/A			
Coupler Height	Adjustable	Suspension	Multi-Leaf Spring		
Deck Height	34"	Ramps	3" Channel 6' Heavy Duty Ramps		
Tongue	10" iBeam Wide Flange	•	, , ,		
Jack	10K Drop Leg Tongue	Uprights	N/A		
Safety Chain	36" x 3/8" 16.2K Capacity	Bump Rail	2" x 2" Square Tube, 6" High		
Wheels	16 x 6 8 - 6.5 Mod (Black)	Lights	Sealed Beam LED D.O.T		
		Decking	2" x 6" #2 or Better Fir Decking		
Tires	ST 235/80 R16 Load Range E	Electric Plug	7-Way Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

