

7K / 10K ALUMINUM TILT BED



STANDARD FEATURES

- 2 5/16" Coupler with 2K Top Wind Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- 2" x 6" #2 or Better Fir Decking
- Channel Tongue (longer than competition)
- Over Center Latch with Release
- Brakes on Both Axles
- Diamond Plate Fenders

POPULAR OPTIONS

- Pressure Treated Decking
- Spare Tire and/or Mount
- Diamond Plate or Smooth Aluminum Decking
- Removable Fenders
- Aluminum Wheels
- Aluminum Diamond Plate Tongue Box

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
SETB716TA2	7' x 16' 7K Tandem Axle Aluminum Tilt Bed	7,000	1,650
SETB718TA2	7' x 18' 7K Tandem Axle Aluminum Tilt Bed	7,000	1,745
SETB716TA3	7' x 16' 10K Tandem Axle Aluminum Tilt Bed	10,000	1,850
SETB718TA3	7' x 18' 10K Tandem Axle Aluminum Tilt Bed	10,000	1,945
SETB720TA3	7' x 20' 10K Tandem Axle Aluminum Tilt Bed	10,000	2,150

7K / 10K ALUMINUM TILT BED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS

GVWR	7,000# (7K) 9,990# (10K)	GAWR	7,000# (7K) 10,400# (10K)
Frame	4" x 2" Tube (7K) 5" x 2" Tube (10K)	Cross Members	3" Channel
Axle	(2) 5,200# Posi-Lube Axle with Brakes	Fenders	10" x 72" Heavy Duty Diamond Plate
Coupler	2 5/16"	Suspension	Multi-Leaf Spring
Coupler Height	16" (7K) 17" (10K)	Ramps	N/A
Deck Height	20" (7K) 21" (10K)	Uprights	N/A
Tongue	5" x 2" Channel	Bump Rail	2" x 2" Tube
Jack	2K Top Wind Tongue	Lights	Sealed Beam LED Lights
Safety Chain	30" x 5/16" 7.6K Capacity	Decking	2" x 6" #2 or Better Fir Decking
Tires	ST 205/75 R15 Load Range C (7K) ST 225/75 R15 Load Range D (10K)	Electric Plug	7-Way RV Molded Water Tight Plug
Wheels	15 x 5 5 - 4.5 Mod (Silver) (7K) 15 x 6 6 - 5.5 Mod (Silver) (10K)	Finish	Aluminum