

7K ULTRALITE SPORT



STANDARD FEATURES

- 2 5/16" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- 2" x 6" #2 or Better Fir Decking
- Channel Tongue (longer than competition)
- Diamond Plate Fenders
- 4' Ramp Gate
- 30" High Round Tube Top Rail
- 24" Ribbed Aluminum Sidewalls

POPULAR OPTIONS

- Pressure Treated Decking
- Spare Tire and/or Mount
- Diamond Plate or Smooth Aluminum Decking
- Aluminum Wheels
- Aluminum Diamond Plate Tongue Box
- Swing Tailgate or Barn Doors
- Stored Heavy Duty Ramps with Barn Doors

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
SEUL610TA2	6' x 10' 7K Tandem Axle Ultralite	7,000	1,145
SEUL612TA2	6' x 12' 7K Tandem Axle Ultralite	7,000	1,220
SEUL6612TA2	6'6" x 12' 7K Tandem Axle Ultralite	7,000	1,260
SEUL712TA2	7' x 12' 7K Tandem Axle Ultralite	7,000	1,295
SEUL714TA2	7' x 14' 7K Tandem Axle Ultralite	7,000	1,365
SEUL716TA2	7' x 16' 7K Tandem Axle Ultralite	7,000	1,435

7K ULTRALITE SPORT TRAILER SPEC SHEET

STANDARD SPECIFICATIONS

GVWR	7,000#	GAWR	7,000#
Frame	2" x 4" Tube	Cross Members	2" x 2"
Axle	(2) 3,500# Posi-Lube Axle with Brakes	Fenders	10" x 72" Diamond Plate
Coupler	2 5/16" Coupler	Suspension	Multi-Leaf Spring
Coupler Height	16"	Ramps	4' Ramp
Deck Height	20"	Uprights	1 1/2" x 1 1/2" Tube
Tongue	4" Channel	Bump Rail	2" Round
Jack	2K Top Wind Tongue	Lights	Sealed Beam LED Lights
Safety Chain	30" x 5/16" 7.6K Capacity	Decking	2" x 6" #2 or Better Fir Decking
Tires	ST 205/75 R15 Load Range C	Electric Plug	7-Way RV Molded Water Tight Plug
Wheels	15 x 5 5 - 4.5 Mod (Silver)	Finish	Aluminum