14K BLACKHAWK ROCK CRAWLER FLATBED DRIVE OVER FENDERS WITH OUTRIGGERS

PICTURES COMING SOON

STANDARD FEATURES

- 2 5/16" Adjustable Coupler
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)
- Brakes on Both Axles
- 5' Heavy Duty Stored Ramps

- 4 D-Rings
- 12K Drop Leg Tongue Jack
- Stake Pockets
- Full Length Heavy Duty Rub Rail
- Spare Tire Mount
- 10" Drive Over Fenders Channel Iron
- Diamond Plate Surface on Outriggers

POPULAR OPTIONS

- Tongue Box Steel or Aluminum Diamond Plate
- · Pressure Treated Decking
- Spare Tire
- Beavertail


- Steel Decking Diamond Plate/Smooth/Sand Texture
- Spring Assisted Heavy Duty Equipment Ramps with Support Elbow

| MODEL | DESCRIPTION | GVWR | CURB WEIGHT |
|-------------|---|--------|-------------|
| BHRC8614TA5 | 8'6" x 14' 14K Blackhawk RC Tandem Axle Flatbed | 14,000 | 2,425 |
| BHRC8616TA5 | 8'6" x 16' 14K Blackhawk RC Tandem Axle Flatbed | 14,000 | 2,555 |
| BHRC8618TA5 | 8'6" x 18' 14K Blackhawk RC Tandem Axle Flatbed | 14,000 | 2,685 |
| BHRC8620TA5 | 8'6" x 20' 14K Blackhawk RC Tandem Axle Flatbed w/ Stabilizer Jacks | 14,000 | 2,835 |
| BHRC8622TA5 | 8'6" x 22' 14K Blackhawk RC Tandem Axle Flatbed w/ Stabilizer Jacks | 14,000 | 2,985 |
| BHRC8624TA5 | 8'6" x 24' 14K Blackhawk RC Tandem Axle Flatbed w/ Stabilizer Jacks | 14,000 | 3,135 |

14K BLACKHAWK RC FLATBED TRAILER SPEC SHEET

| STANDARD SPECIFICATIONS | | | | | |
|-------------------------|---|---------------|----------------------------------|--|--|
| GVWR | 14,000# | GAWR | 14,000# | | |
| Frame | 6" Channel | Cross Members | 3" Channel, 16" on Center | | |
| Axle | (2) 7,000# Posi-Lube Axle w/ Brakes | | | | |
| Coupler | Adjustable 2 5/16" | Fenders | 10" Channel Drive Over | | |
| Coupler Height | Adjustable | Suspension | Multi-Leaf Spring | | |
| Deck Height | 24" | Ramps | 5' Stored Heavy Duty | | |
| Tongue | 2" x 5" Rectangular Tube | Uprights | N/A | | |
| Jack | 12K Drop Leg Tongue | oprigits | IVA | | |
| Safety Chain | 36" x 3/8" 16.2K Capacity | Bump Rail | 2" x 2" Rectangle Tube, 6" High | | |
| Wheels | 16 x 6 8 - 6.5 Mod (Black) | Lights | Sealed Beam LED D.O.T | | |
| | | Decking | 2" x 6" #2 or Better Fir Decking | | |
| Tires | ST 235/80 R16 Load Range E | Electric Plug | 7-Way Molded Water Tight Plug | | |
| Finish | Steel is cleaned (wiped down) to ensure quality protective finish | Paint | PPG Primer and Paint | | |

STANDARD COLORS



OPTIONAL COLORS

