

3.5K STERLING UTILITY DUMP



STANDARD FEATURES

- Power Up Power Down Electric/Hydraulic Pump
- Direct Push Cylinder
- 18" side to top rail
- Bi-fold gate
- Aluminum wheels
- Sealed Beam LED Lights
- Swing up jack with wheel
- 5" Tube Tongue and Frame (upgraded heavy duty version)
- 4" Cross Members
- Ramps and Ramp Bar
- 110 Battery Charger
- Extruded Aluminum Decking
- D-Rings

POPULAR OPTIONS

- Spare Tire Mount / Spare Tire

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
SS508ADT	5' x 8' 3.5K Sterling Single Axle Utility Dump	3,500	470
SS510ADT	5' x 10' 3.5K Sterling Single Axle Utility Dump	3,500	540
SS610ADT	6' x 10' 3.5K Sterling Single Axle Utility Dump	3,500	590

3.5K STERLING UTILITY DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS

GVWR	3,500#	GAWR	2,500#
Frame	5" x 2" Tube	Cross Members	5" Tube
Axle	3,500# Torsion Axle	Fenders	Aluminum
Coupler	2" x 3"	Suspension	Multi-Leaf Spring
Coupler Height	17"	Ramps	18" Extruded Aluminum
Deck Height	21"	Uprights	2" x 3" Tube
Tongue	5" x 2" Tube	Bump Rail	2" x 2"
Jack	Swing Up Jack w/ Wheel	Lights	Sealed Beam LED Lights
Safety Chain	30" x 5/16" 7.6K Capacity	Decking	#2 Extruded Aluminum
Tires	ST 185/80 R14 Load Range D	Electric Plug	7-Way RV Molded Water Tight Plug
Wheels	14R Aluminum Rims	Finish	Aluminum