

# 10K EAGLE ROCK CRAWLER FLATBED

## DRIVE OVER FENDERS WITH OUTRIGGERS



### STANDARD FEATURES

- 2 5/16" Adjustable Coupler
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)
- Brakes on Both Axles
- 6" Bump Rail
- 5' Heavy Duty Stored Ramps
- 4 D-Rings
- 1/8" Diamond Plate Surface Outriggers
- 10" Drive Over Fenders (channel), 82" Between
- Sand Texture over Fenders
- 7K Drop Leg Tongue Jack

### POPULAR OPTIONS


- Tongue Box Steel or Aluminum Diamond Plate
- Pressure Treated Decking
- Spare Tire and/or Mount
- Beavertail
- Steel Decking Diamond Plate/Smooth/Sand Texture
- Full Length Rub Rail

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
EFBRC8610TA3	8'6" x 10' 10K Eagle RC Tandem Axle Flatbed	10,000	1,770
EFBRC8612TA3	8'6" x 12' 10K Eagle RC Tandem Axle Flatbed	10,000	1,875
EFBRC8614TA3	8'6" x 14' 10K Eagle RC Tandem Axle Flatbed	10,000	2,110
EFBRC8616TA3	8'6" x 16' 10K Eagle RC Tandem Axle Flatbed	10,000	2,215
EFBRC8618TA3	8'6" x 18' 10K Eagle RC Tandem Axle Flatbed	10,000	2,320
EFBRC8620TA3	8'6" x 20' 10K Eagle RC Tandem Axle Flatbed w/ Stabilizer Jacks	10,000	2,445
EFBRC8622TA3	8'6" x 22' 10K Eagle RC Tandem Axle Flatbed w/ Stabilizer Jacks	10,000	2,570


# 10K EAGLE RC FLATBED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS			
<b>GVWR</b>	9,900#	<b>GAWR</b>	10,400#
<b>Frame</b>	5" Channel	<b>Cross Members</b>	3" Channel
<b>Axle</b>	(2) 5,200# Posi-Lube Axle w/ Brakes	<b>Fenders</b>	82" Between Fenders Drive on/Drive off 10" Channel
<b>Coupler</b>	Adjustable 2 5/16"	<b>Suspension</b>	Multi-Leaf Spring
<b>Coupler Height</b>	17"	<b>Ramps</b>	5' Stored Heavy Duty
<b>Deck Height</b>	23"	<b>Uprights</b>	N/A
<b>Tongue</b>	2" x 5" Rectangular Tube	<b>Bump Rail</b>	2" x 2" Rectangle Tube, 6" High
<b>Jack</b>	7K Drop Leg Tongue	<b>Lights</b>	Sealed Beam LED D.O.T
<b>Safety Chain</b>	36" x 5/16" 11.7K Capacity	<b>Decking</b>	2" x 6" #2 or Better Fir Decking
<b>Wheels</b>	15 x 6 6 - 5.5 Mod (Silver)	<b>Electric Plug</b>	7-Way Molded Water Tight Plug
<b>Tires</b>	ST 225/75 D15 Load Range D	<b>Paint</b>	PPG Primer and Paint
<b>Finish</b>	Steel is cleaned (wiped down) to ensure quality protective finish		

## STANDARD COLORS




Black ALK-FP901



Eagle Majestic Grey

## OPTIONAL COLORS



White ALK-FP951



Bright Yellow ALK-FP801



Cat Yellow ALK-FP827



Ford Blue ALK-FP101



Ice Gray ALK-FP301



John Deer Green ALK - FP401



Kubota Orange ALK-FP601



Case IH Red ALK-FP701