

STANDARD FEATURES

- Adjustable 2 5/16" Coupler w/ 12K Spring Jack
- Stake Pockets
- Tube Tongue (Longer than competition)
- Trickle Charge Line From Tow Vehicle
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- Electric/Hydraulic Pump with Reservoir and Gravity Override
- PPG Primer and Paint

- Lockable Tongue Box
- Heavy Duty Ramps 7'
- Spare Tire Mount
- Front and Rear Diamond Plate Fender Mega Steps
- 4 D Rings
- Metal Cover Mesh Tarp Roll System
- Heavy Duty Diamond Plate Fenders
- 8 gauge Floors & Sidewalls
- GPS Tracker

POPULAR OPTIONS

- Spare Tire
- 24" Expanded Metal Mesh or Solid Side Extensions


Gooseneck Option

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
VP24714TA5	7' x 14' 14K Venture Pro Tandem Axle Dump, 24" Sides	15,400	3,380
VP36714TA5	7' x 14' 14K Venture Pro Tandem Axle Dump, 36" Sides	15,400	3,680
VP48714TA5	7' x 14' 14K Venture Pro Tandem Axle Dump, 48" Sides	15,400	4,200

14K VENTURE PRO DUMP TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	15,400#	GAWR	15,400#		
Main Frame	6" Channel 4" Channel Cross Members	Floor	8 gauge Steel		
Axle	Dexter Ax 7,000# Chambered				
Coupler	2 5/16" Adjustable Coupler	Fenders	Heavy Duty Walk On		
Hoist	Electric/Hydraulic Scissor Hoist (45° dump angle or more) 21K Scissor Lift	Suspension	Multi-Leaf Spring		
Coupler Height	Adjustable	Ramps	3" Channel Heavy Duty 7' Ramps		
Deck Height	26"	Uprights	4" x 2" x 0.120" Rectangle Tube		
Tongue	2" x 6" Rectangle Tube (.120 thick wall)	Top Rail	8 gauge Formed		
Jack	12K Spring Loaded	Lights	Sealed Beam LED D.O.T		
Safety Chain	36" x 3/8" 16.2K Capacity	Decking	8 gauge Steel Floor		
Tires	ST 235/80 R16 Load Range E	Electric Plug	7-Way RV Molded Water Tight Plug		
11103	Steel is cleaned (wiped down) to ensure quality protective finish	Wheels	16 x 6 8-6.5 Mod (Black)		
Finish		Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

