

STANDARD FEATURES

- 2 5/16" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D-Rings
- 2" x 6" #2 or Better Fir Decking

- Rectangle Tube Tongue (longer than competition)
- Brakes on Both Axles
- Stake Pockets
- Stored 5' Heavy Duty Ramps
- 84" Between Fenders

POPULAR OPTIONS

- Tongue Box Steel or Aluminum Diamond Plate
- · Pressure Treated Decking


• Spare Tire and/or Mount

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
FAFB512TA2	5' x 12' 7K Tandem Axle Angle Flatbed	7,000	1,185
FAFB612TA2	6' x 12' 7K Tandem Axle Angle Flatbed	7,000	1,285
FAFB712TA2	7' x 12' 7K Tandem Axle Angle Flatbed	7,000	1,325
FAFB714TA2	7' x 14' 7K Tandem Axle Angle Flatbed	7,000	1,400
FAFB716TA2	7' x 16' 7K Tandem Axle Angle Flatbed	7,000	1,530
FAFB718TA2	7' x 18' 7K Tandem Axle Angle Flatbed	7,000	1,620
FAFB720TA2	7' x 20' 7K Tandem Axle Angle Flatbed	7,000	1,730


7K ANGLE FLATBED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	7,000#	GAWR	7,000#		
Frame	5" x 3" Angle	Cross Members	2" x 2" Angle		
Axle	(2) 3,500# Posi-Lube Axles with Brakes	Cross members			
Coupler	2 5/16" Coupler	Fenders	84" Width Between Fenders 9" x 66" Fender		
Coupler Height	17"		3 x 00 reliuel		
Deck Height	19"	Suspension	Multi-Leaf Spring		
Tongue	2" x 4" Rectangular Tube	Ramps	5' Stored Heavy Duty		
Jack	2K Top Wind Tongue	Uprights	N/A		
Safety Chain	30" x 5/16" 7.6K Capacity	Bump Rail	2" x 2" Rectangle Tube, 6" High		
Wheels	15 x 5 5 - 4.5 Mod (Silver)	Lights	Sealed Beam LED D.O.T		
		Decking	2" x 6" #2 or Better Fir Decking		
Tires	ST 205/75 D15 Load Range C	Electric Plug	7-Way Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



Black ALK-FP901



Eagle Majestic Grey

OPTIONAL COLORS

