

STERLING FENDER HIGH UTILITY



STANDARD FEATURES

- Aluminum wheels
- Sealed Beam LED Lights
- Swing up jack with wheel
- 4" Tube Tongue and Frame (upgraded heavy duty version)
- 4" Cross Members
- Ramps and Ramp Bar
- 110 Battery Charger
- Extruded Aluminum Decking
- D-Rings

POPULAR OPTIONS

- Spare Tire Mount / Spare Tire

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
SSOS508SA	5' x 8' Sterling Single Axle Fender High Utility	2,990	300
SSOS510SA	5' x 10' Sterling Single Axle Fender High Utility	2,990	325
SSOS610SA	6' x 10' Sterling Single Axle Fender High Utility	2,990	360
SSOS612SA	6' x 12' Sterling Single Axle Fender High Utility	2,990	380

STERLING FENDER HIGH UTILITY TRAILER SPEC SHEET

STANDARD SPECIFICATIONS

GVWR	3,500#	GAWR	2,500#
Frame	Tubular Aluminum	Cross Members	4" Tube
Axle	3,500# Torsion Axle w/ Grease Zerk	Fenders	Diamond Plate Aluminum
Coupler	2"	Suspension	Multi-Leaf Spring
Coupler Height	17"	Ramps	4' Aluminum Bi-Fold Gate
Deck Height	21"	Uprights	2" x 3" Tube
Tongue	3" x 2" Tube	Bump Rail	2" x 2"
Jack	2K Swing Up Jack w/ Wheel	Lights	Sealed Beam LED Lights
Safety Chain	30" x 5/16" 7.6K Capacity	Decking	#2 Extruded Aluminum
Tires	ST 205 R14 Load Range D	Electric Plug	7-Way RV Molded Water Tight Plug
Wheels	14R Aluminum Rims	Finish	Aluminum