



TECHNICAL DATA SHEET

Foaming Lubricant & Protectant

▶ Item Number: 25-173 ▶ 50 State Compliant

Product Overview

Foaming Lubricant & Protectant is a foaming aerosol lubricant combining high-viscosity base oils with anti-wear and corrosion inhibiting additives to deliver a more substantial, longer-lasting lubricating film than conventional thin sprays. Particularly effective on vertical and irregular surfaces where runoff and lubricant loss are concerns.

Key Features and Benefits

- Foaming - bodied high duration lubricant
- Antiwear and corrosion-inhibiting protection
- Outperforms thin general-purpose sprays

Typical Applications

- Hinges, linkages, and slides
- Cables, chains, and rollers
- Vertical and hard-to-reach lube points

Typical Properties

Property	Typical Value
Apperance/Color	Amber to light amber liquid in aerosol package
Odor	Mild petroleum / solvent
Form	Foaming aerosol
Flammability	Extremely flammable aerosol
Density	7.7 lb/gal
Propellant	Hydrocarbon propellant

Directions to Use

- 1.Shake well and spray directly onto the lubrication point.
- 2.Allow foam to expand, wet the surface, and settle into the contact area.
- 3.Cycle the part if possible to help distribute the lubricant.

VOC Information	<10% VOC foaming lubricant
Storage and Handling	Store in a cool, dry, well-ventilated area away from direct sunlight. Do not expose containers to temperatures above 120°F.
Transportation	UN1950 Aerosols
Safety Information	Flammable aerosol. Contents under pressure. Use in well-ventilated area.