

Strap-Tight Band and Buckle Strapping System

The Murray Strap-Tight Band and Buckle Strapping system consists of stainless steel strapping, buckles and tool to connect hoses, or to attach signs to posts.

- Strapping and buckle materials available include AISI grades 201, and 304. Other materials may be available upon request
- Material edge is made without burrs to protect users from injury. The high-quality material will securely tighten without snapping, when properly installed
- Various packaging configurations and coil lengths available upon request
- Applications include: Outdoor and indoor signage, security cameras, petro-chemical plants, thermoelectric power stations, shipyard industry and marine, high pressure rubber type hoses, general industry, railway, aerospace, agricultural machinery, and many others.

Part Numbers - Strap-Tight Bands					
AISI 201	AISI 304	Band Width (in)	Thickness (in)		
SCB25X201	SCB25X304	1/4"	0.018		
SCB37X201	SCB37X304	3/8"	0.021		
SCB50X201	SCB50X304	1/2"	0.025		
SCB62X201	SCB62X304	5/8"	0.025		
SCB75X201	SCB75X304	3/4"	0.027		

Standard roll length is 100 ft. Other lengths available upon request. Rolls packaged inindividual dispenser cartons, then in a master carton.

Part Numbers - Strap-Tight Buckles					
AISI 201	AISI 304	Band Width (in)	Thickness (in)		
SCA25X201	SCA25X304	1/4"	0.03		
SCA37X201	SCA37X304	3/8"	0.11		
SCA50X201	SCA50X304	1/2"	0.22		
SCA62X201	SCA62X304	5/8"	0.22		
SCA75X201	SCA75X304	3.4"	0.22		

Buckles packed 100 pcs per bag.

Installation Tool

Allows for full installation by pulling band through buckle, tightening using this tool, and safely cutting excess banding. Final installation will require a hammer to fold down tabs. Follow installation instructions included with the tool.

Part Number: SCT001





