



ANCHOR PRODUCTS®

Connections That Last

The U-3400 Series Anchor is a lightweight, leak-proof rooftop attachment system consisting of a U-Anchor 3000 Series plate with a factory-sealed cover membrane. Available in KEE, TPO, EDPM, and PVC options, it provides a watertight, manufacturer-approved attachment for mechanically attached or fully adhered single-ply membranes. Accepted by major roofing manufacturers, the U-3400 secures rooftop equipment quickly, safely, and effectively, making it a versatile choice for any project.



U-ANCHOR®

U3400 Anchor



Front



Back

Equipment Attachment

- The U3400 Anchor is attached by fastening through the roofing assembly into the structural decking with 2-12 approved fasteners.
- The membrane cover is hot air welded around the perimeter to the roof membrane.
- To mount rooftop equipment, the dual connection nuts must be fastened to approximately 20-25 lbf-ft using a calibrated torque wrench. Excessive torque may damage the U-Anchor.
- Material Compatibility: Stainless steel bolts; all attachments tested as a system and designed to be compatible.

Warranty

- 20 Year Guarantee on waterproofing or match of current roof warranty



U-Anchor Advantages

- Extremely strong; lightweight.
- Fast installation — installs in less than five minutes.
- Can be installed on surfaces from flat to vertical (parapet).
- Completely watertight when installed properly.



**ANCHOR
PRODUCTS®**
Connections That Last

Product Specs

Tested in accordance with FM 4481 Section 4.1 over 1/2 Steel. Assembly-specific results may vary. Please contact Anchor Products® directly for additional testing results and information.

• Bolt

(2) 3/8"-16 x 1-3/8" Bolt*

Material Type: 304 Stainless Steel

• Plate

Size: 11" x 5.5"

Fastener Holes: Ø 0.265 (12 holes)

Material Thickness: 0.047 (1.19 mm)

Material Type: G90 Galvanized Steel

• Cover Membrane

Manufacturer: Brand and Non-Brand Specific

Color: White (Other colors available)

Length: 17.50

Width: 11.75

Thickness: Approx. 60 mils

Membrane Types: PVC, KEE, TPO, or EPDM (depending on model)

• Patents


Visit www.anchorp.com/resources/patents

Packing Specs

- Sold Individually OR Full Box Quantity
- Individual Weight: Approx. 1.4 lbs.
- Full Box Quantity: 10 units
- Box Weight: Approx. 17 lbs.
- Box Dimensions: 19"x 14"x 14"
- Full Pallet Quantity: 24 boxes
- Pallet Dimensions: 40"x 48"x 61"



U3400 Anchor Dimensional Drawing



Membrane Options

TPO	ELEVATE, GEN FLEX, JM, MULE, HIDE, CARLISLE, DURO-LAST, GAF, IKO, VERSICO
PVC\KEE	ELEVATE, GEN FLEX, JM, MULE, HIDE, CARLISLE, DURO-LAST, FIBERTITE, FLEX, GAF, IB, IKO, SIKA SARNAFIL, VERSICO, WEATHER BOND
EDPM	ELEVATE, GEN FLEX, JM, MULE, HIDE, CARLISLE, VERSICO

Hardware

ROOF TYPE	HARDWARE KIT
METAL DECK (24ga MIN)	(8) #14 or #15 ROOF FASTENERS
PLAYWOOD SHEETING (3/4" MIN)	(8) #14 ROOF FASTENERS
PARTICLE SHEETING (1" MIN)	(8) #14 ROOF FASTENERS
CONCRETE DECK (STD WEIGHT)	(6) #14 CONCRETE FASTENERS



Call Us Now!
888-575-2131

[For Warranty Information](#)

anchorp.com

* Specified option is standard. Custom options may be available for additional charge. Lead times may apply depending on roofing manufacturer and product availability.

© Anchor Products

6316 Airport Fwy. Ste. D, Haltom City, TX 76117

Revised Aug 2025

Connections That Last

