



PERFORMANCE

Low pressure output	80m ³ /hr
Low pressure	70bar
High pressure output	50m ³ /hr
High pressure	125bar

TECHNICAL INFORMATION

Concrete cylinder dimension	Φ200×1600mm
Hydraulic cylinder	Φ125×1600mm
Hydraulic cylinder rod dimension	Φ80
Max. stroke	32/Min
Main hydraulic pump	Rexroth A11VO190 & A10V028

H/L Pressure switch device	Auto
Variable volume control	0 to full
Hopper height	1240mm
Outlet diameter	6 Inch
<i>PTO</i>	
Manufacturer	STIEBEL 4496
<i>CONFIGURATION</i>	
Circuit type	Open
High-low pressure shifting	Fully Auto
Lubricating system	Auto grease
6 Channel Wireless remote control	Autec
Distribution Valve Style	Butterfly Valve
Manual stroke	√

High Pressure Gerni	√
Vibrator Motor	√
Inbuilt Tool Box	√
Water Tank	√
TRUCK	
Manufacturer's model	FUSO FK62FLZRFAC
GVM	12,000kg
Wheelbase	4870mm
<i>DIMENSIONS AND WEIGHT (APROX.)</i>	
Length	8300mm
Width	2170mm
Height	2000mm
Weight	9000kg (Front: 2940kg, Rear: 6060kg)