

HYDROSTATIC TROWEL - STX6H



HTX6H

- All new liquid cooled 70HP Hatz 4H50TIC turbo diesel engine complies with US EPA Tier 4 Final emissions requirements.
- Patented Engine Power Management senses engine load and adjusts hydraulic pump stroke to allow the engine to operate at peak efficiency.
- Low centre of gravity produces stability while minimizing oversteer. Optimizes steering feedback and operator control.
- Cruise control reduces operator fatigue during low speed operations.
- Six blade spider assemblies assure the flattest floors possible with 33% more blade contact.
- SmartPitch™ control synchronizes blade pitch for both rotors with a single button.
- 6 LED lights provide state of the art illumination for night time or indoor work.
- 12 Volt outlet and drink holder for charging your electronic devices and operator convenience.
- Retardant spray system, actuated by controls located on the steering handles, provides uniform coverage of the slab surface.
- Adjustable seat features armrests and essential back support. All controls and warning lights are convenient to the operator.



Proportional hydraulic steering and joystick controls allow precision performance with minimal effort, preventing operator fatigue.



Multifunction display provides operator with easy-to-read data including engine speed, fuel levels and alerts.



Clam shell design simplifies maintenance and offers the convenient access to all serviceable components.

HYDROSTATIC TROWEL - SPECIFICATIONS

Model	Engine	HP (kw)	Engine Cooling	Path Width in. (cm)	LxWxH in. (cm)	Rotor RPM	Blades Per Rotor	Steering Type	Run Time gal./hr. (ltr/hr)	Fuel Tank Capacity gal (ltr)	Operating Weight lb.(kg)	Wheel kit*
Twin 60" Non-Overlapping												
STXDF	Ford Powered Products	84(63)	Liquid	117 (2971)	125x65x57 (317x165x144)	150	6	Hydraulic		18(68)	2600 (1179)	
STX6H	Hatz 4H50TIC	70	Liquid	117 (297)	125x65x57 (317x165x144)	0-130	6	Proportional Hydraulic	3.4	20 (75.7)	2544 (1153)	EMR3
Twin 48" Non-Overlapping												
HTXG6DF	Power Solutions International (PSI)	68	Liquid	92 (233)	95x48x57 (241x122x145)	10-160	6	Proportional Hydraulic	1.46 (5.52)	11 (42)	2133 (968.6)	EMR3
HTX6H	Hatz 4H50TIC	70	Liquid	92 (233)	95x48x59 (241x122x149)	0-160	6	Proportional Hydraulic	3.2	10 (37.85)	2345 (1063)	EMR3