



**ST1**  
**US MOBILE UNIT**  
**INFORMATION**

Updated 06/03/2026

## Single Trailer Support Unit

# ST1: TECHNICAL SPECIFICATIONS

### DIMENSIONS

- CURBSIDE EXPANDO
- 53' LONG X 8'6" WIDE X 13'6" HIGH
- 78'11" LONG X 16'12" WIDE X 13'6" HIGH - EXPANDED WITH TRACTOR
- 58'11" LONG X 16'12" WIDE X 13'6" HIGH - EXPANDED WITHOUT TRACTOR

### PRODUCTION

- 8 FULL OPERATING WORKING POSITIONS WITH KP12S, WOHLERS, AND ROUTER PANELS
- 1 TECH MANAGER STATION
- KVM SUPPORT FOR ALL WORKSTATIONS FROM A UNIT
- MONITORS FED FROM A UNIT

### CAMERAS

- 1 SONY HDLA LARGE LENS ADAPTER
- 1 HARD CAMERA PANHEAD & TRIPOD

### LENSES

- 1 FUJINON 101X8.9 HARD LENS

### SUPPORT EQUIPMENT

- CARGO AREA HAS 2 OPERATING POSITIONS
- MONITORS: **8** -21.5" LED, **2** -27" LED, **3** -32" LED
- 3 PUSH CARTS
- 1 LIGHT KIT

### MICROPHONES

- 28 SHORT SHOTGUN MICROPHONES
- 25 STICK MICROPHONES

### AUDIO

- CALREC ARTEMIS BEAM DIGITAL AUDIO CONSOLE
- 48 FADERS
- 32 X 32 MIC/LINE CHANNELS
- 32 AES INPUTS X 32 AES OUTPUTS
- 2 MADI INPUTS X 2 MADI OUTPUTS
- 6 DBX 160X LIMITER
- 1 DBX 1046 4 CHANNEL COMPRESSOR/LIMITER
- 12 SOUND DEVICES MP1 LINE AMPS
- HYDRA 48/16 (FRONT XLR) IN EDIT ROOM FOR AUDIO INTERFACE
- 1 CD PLAYER

### CABLES

- TAC 4 MILITARY: 1 -1000', 4 -500'
- TAC 4 ST-ST: 1 -1000', 1-500' 3 -300' OR LESS
- TAC 6 ST-ST: 3 -500'
- TAC 12 ST-ST: 8 -1500' 5 -1000' 9 -500' 13 -250' 8 -150' OR LESS
- 9MM SMPTE: 5 -500' 12 -250' 10 -100' 8 -50' 2 -25'
- 9MM SMPTE MULTS: 2 (5X100')
- 5 PAIR HD COAX LOOMS: 5 -25'
- DT12: 6 -250' 8 -100'
- DT12 FANOUTS: 6
- DT12 BREAKOUT BOXES: 4
- 6 PAIR XLR: 2 -200' 2 -100'
- 4 PAIR XLR: 2 -250' 3 -200'
- MARRIED PAIR XLR: 1 -100' 6 -50'
- ASSORTED SINGLE LINE XLR
- ASSORTED COAX

