



H1 US MOBILE UNIT INFORMATION

Updated 06/01/2026



Single Trailer Unit Based in Hawaii

H1: TECHNICAL SPECIFICATIONS

POWER REQUIREMENTS

- 2 - 208V, 200 AMPS 3 PHASE 150' CAMLOCK

PRODUCTION SWITCHER

- GVG KAYENNE CLASSIC SWITCHER, 5 ME

CAMERAS

- 2 SONY HDC3300 SUPERSLOMO CAMERA (UPON REQUEST)
- 14 SONY HDC1500 CAMERA
- 8 SLEDS
- 8 HEAVY PANHEAD W/STICKS
- 5 LIGHTWEIGHT STICKS
- 2 CLOCK CAMERA

LENSES

- 6 HARD LENSES
- 4 HANDHELD LENSES
- 2 WIDE ANGLE LENSES

RECORD & PLAYBACK

- 3 EVS XT3 12 CHANNEL LSM 10 GB
- 4 EVS XT3 8 CHANNEL LSM 10 GB
- 1 EVS XT3 4 CHANNEL SPOT BOX 10 GB
- 2 EVS X-FILE3 10 GB

AUDIO

- CALREC SIGMA DIGITAL AUDIO CONSOLE WITH 64 DUAL LAYER FADERS

COMMUNICATIONS

- ADAM INTERCOM SYSTEM - 112 PORTS

SUPPORT EQUIPMENT

- PESA ROUTER
- HD VIDEO - 288 INPUTS X 480 OUTPUTS
- AES 128 INPUTS X 128 OUTPUTS
- ANALOG AUDIO 256 INPUTS X 256 OUTPUTS
- 20 FRAME SYNCs WITH COLOR CORRECTORS
- 2 AJA FS2 FRAME SYNCs
- 2 AJA FS4 FRAME SYNCs
- 1 FIBER BOOTH FIELD KIT
- BASIC TRUCK COMPLIMENT OF CABLE, MICS, ETC.



H1

FLOORPLAN



