



SUPERSHOOTER 12

US MOBILE UNIT

INFORMATION

Updated 05/29/2026

NEPGROUP.COM



IP-Based, TFC Driven, 1080i, 720p, 1080p & HDR Capable | Travels with support unit, ST10

SUPERSHOOTER 12: TECHNICAL SPECIFICATIONS

POWER REQUIREMENTS

- SS10 REQUIRES 1 400A OR 2 200A SERVICES
- ST10 REQUIRES 1 200 AMP SERVICE REQUIRED

PRODUCTION SWITCHER

- KAYENNE X-FRAME, 8.5 M/E

CAMERAS

- 8 SONY HDC5500 CAMERAS
- 5 SONY HDC3500 CAMERAS
- 2 SONY HDC 2500 CAMERAS
- 8 SLEDS
- 8 HEAVY PANHEAD W/STICKS
- 8 HANDHELD STICKS
- 1 ENG KIT

LENSES

- 8 CANON 122X HARD LENS
- 6 CANON 24X HANDHELD LENS
- 3 CANON 20X5 WIDE ANGLE LENS
- 2 CANON 14X4.3 WIDE ANGLE LENS

RECORD/REPLAY

- 5 EVS XT-VIA 12 CHANNEL
- 1 EVS XS VIA 6 CHANNEL SPOT BOX
- 2 EVS XFILE3
- 2 EVS IP DIRECTOR
- 2 EVS XT ACCESS
- 1 KIPRO-GO USB RECORDER

AUDIO

- CALREC ARGO Q WITH 60 DUAL FADERS
- IMPULSE CORE (AOIP)
- 2 WAVE SERVER
- 1 NEURAL UP MIX/DOWN MIX PACKAGE
- 2 DIGICART

MICROPHONES

- 14 ANNOUNCER HEADSETS
- 6 DALTEC ANNOUNCE CONSOLES
- 8 STUDIO TECH ANNOUNCE CONSOLES
- 2 GLENSOUND ANNOUNCE CONSOLES
- 14 SHORT SHOTGUN MICROPHONES
- 8 LONG SHOTGUN MICROPHONES
- 8 STEREO SHORT SHOTGUN MICROPHONES
- 16 STICK MICROPHONES
- 8 LAVALIER MICROPHONES

COMMUNICATIONS

- ADAM INTERCOM SYSTEM - 368 PORTS
- 20 DUAL LISTEN BELTPACKS
- 1 DANTE QUAD LISTEN BELTPACKS
- 20 SINGLE MUFF HEADSETS
- 20 DOUBLE MUFF HEADSETS
- 12 IFB BELTPACKS
- 10 DANTE IFB BELTPACKS
- 12 WALKIE TALKIES WITH 2 BASE STATIONS
- 1 PHONE SYSTEM WITH 16 LINES
- 8 TIF - TELEPHONE INTERFACES
- 4 QKT

SUPPORT EQUIPMENT

- NEP TFC IP ROUTER
- HD VIDEO - 352 INPUTS X 328 OUTPUTS
- 234 INPUTS X 253 OUTPUT EMBED/DE-EMBED
- MADI 18 INPUTS X 18 OUTPUTS
- AES 96 INPUTS X 96 OUTPUTS
- ANALOG AUDIO 96 INPUTS X 96 OUTPUTS
- 10 HD VIDEO OVER FIBER TRANSMITTERS
- 2 AJA FSHDR FRAME SYNCs
- 2 AJA FS4 FRAME SYNCs
- 20 UDX WITH COLOR CORRECTORS
- 2 FIBER FIELD/BOOTH KITS
- 3 HYDRA BOXES
- 2 32X32 AT300 KITS
- 1 LIGHT KIT
- MONITORS: 4 -21" LCD, 6 -18" LCD, 4 -17" LCD

CABLES

- 9MM SMPTE: 2 -500' 10 -250' 12 -100' 10 -50' 15 -25'
- 9MM SMPTE MULT: 2 (6 X 125') 1 (7X100)
- MINI TRIAX: 2 -500' 10 -250' 8 -100' 8 -25'
- MINI TRIAX MULT: 1 (6 X 125')
- DT12: 1 -500' 6 -250' 10 -125' 4 -50'
- 10 DT12 FANOUT SETS
- 8 DT12 BREAKOUT BOX(ES)
- 6 PAIR MULT 2 -100'
- 4 PAIR MULT 4 -100' 4 -50' 4 -25'
- MARRIED PAIR: 6- 25'
- ASSORTED SINGLE LINE XLR
- TAC-12 ST TO ST: 2 -1500' 2 -1000' 6 -500' 6 -250' 8 -150'
- TAC-12 FANOUT: 4
- 10 PAIR HD COAX LOOM 6 -25'
- 32 PAIR HD COAX LOOM 4 -25'
- ASSORTED SINGLE LINE COAX
- 6 SETS OF 75' 4/0 CAMLOCK POWER CABLE

