



SUPERSHOOTER 65

US MOBILE UNIT

INFORMATION

Updated 08/04/2026

NEPGROUP.COM



1080i, 720p, 1080p & HDR Capable | Single Trailer REMI Unit

SUPERSHOOTER 65: TECHNICAL SPECIFICATIONS

POWER REQUIREMENTS

- REQUIRES 1 200 AMP SERVICE

COMMUNICATIONS

- ADAM INTERCOM SYSTEM - 96 PORTS
- 1 RVON 16 CARD
- 8 IFB BELTPACKS
- 16 SINGLE MUFF HEADSETS
- 16 DOUBLE MUFF HEADSETS
- 4 TIF

CAMERAS

- 2 SONY HDC2500 CAMERA (Clock Camera)
- 8 SONY HDC3500 CAMERA
- 4 Sony HDC5500 CAMERA
- 8 SONY HDLA LARGE LENS ADAPTER
- 8 HARD CAMERA PANHEAD & TRIPOD
- 4 HH CAMERA PANHEAD & TRIPOD
- 14 CCUS ON BOARD

LENSES

- 2 CANON 122X HARD LENS
- 6 CANON 95X HARD LENS
- 4 CANON 22X HANDHELD LENS
- 2 CANON 20X HANDHELD LENS
- 4 CANON 4.3X WIDE ANGLE LENS

SUPPORT EQUIPMENT

- ROSS 12G ULTRIX, 144X144 WITH MULTIVIEWER
- FULL EMBED/DE-EMBED
- FRAME SYNC LICENSE
- 7 AJA FS HDR FRAME SYNC
- 8 UDX CONVERTERS
- 12 VIDEO OVER FIBER TRANSMITTERS
- 1 TSI TALLY SYSTEM
- MONITORS: 9 -21" 2 -19' LCDS

AUDIO

- CALREC SUMMA DIGITAL AUDIO CONSOLE WITH BLUEFIN 2
- 44 FADER
- 32 AES INPUTS & 32 AES OUTPUTS
- 6 MADI INPUTS & 6 MADI OUTPUTS
- 2 HYDRA II FIELD BOXES (24X8)
- 2 FIBER BOOTH FIELD KITS
- 1 MONO TO STEREO

MICROPHONES

- 4 ANNOUNCER HEADSETS
- 4 DALTECH TALKBACK BOXES
- 12 SHORT SHOTGUN
- 12 LONG SHOTGUN
- 8 STICK MICROPHONES
- 12 LAVALIER MICROPHONES

RECORD AND PLAYBACK

- 2 EVS XT3 12 CHANNEL

GRAPHICS

- UPON REQUEST

CABLES

- 9MM SMPTE: 7 -500' 8 -250' 8 -100' 5 -50' 12 -25'
- 9MM SMPTE MULT: 3 (6X150')
- TAC-12 ST TO ST: 2 -1500' 2 -1000' 6 -500' 8 -250' 2 -150' OR LESS
- TAC 12 ST TO ST: 4 FANOUTS
- TAC 4 ST TO ST: 2 -300' OR LESS
- MINI TRIAX: 2 -500' 8 -250' 7 -100' 8 -50'
- 2 MINI TRIAX LOOMS
- DT12: 4 -500' 6 -250' 6 -125'
- 6 DT12 FANOUT SETS
- 1 SET OF 75' POWER CABLE



SUPERSHOOTER 65

FLOORPLAN

