



XP-1

US MOBILE UNIT INFORMATION

Updated 08/07/2026

1080i & 720p Capable | Sprinter Van Based in Hawaii

XP-1: TECHNICAL SPECIFICATIONS

DIMENSIONS

- MERCEDES SPRINTER MODEL 3500E VAN
- 24' LONG X 9'3" HIGH X 6'8" WIDE

POWER REQUIREMENTS

- 110 VOLTS, SINGLE PHASE, 30 AMPS

PRODUCTION

- FOR-A MVS-1000 HANABI SWITCHER, 12 INPUTS / 6 OUTPUTS, 1.5 ME

COMMUNICATIONS

- RTS CRONUS MATRIX SYSTEM - 32 PORTS
- 5 DUAL LISTEN BELTPACKS
- 10 SINGLE MUFF HEADSETS
- 10 DUAL MUFF HEADSETS
- 4 IFB BELTPACKS
- 2 TIF - TELEPHONE INTERFACE

CAMERAS

- 5 GVG LDK6000 CAMERA
- 2 GVG LDK6000 SUPER EXPANDERS
- 1 HH CAMERA PANHEAD & TRIPOD
- 2 HARD CAMERA PANHEAD & TRIPOD
- TRUCK WIRED FOR 5 CCU'S
- ADDITIONAL CAMERA MAKES AND MODELS AVAILABLE ON REQUEST

LENSES

- 3 CANON 21:1 HANDHELD LENS
- 2 CANON 75X9.3B HARD LENS

SUPPORT EQUIPMENT

- 3 UTILITY FRAME SYNC/PROCESSORS
- 2 HD VIDEO OVER FIBER TRANSMITTERS
- MONITORS:
- 1 - 20" COLOR

AUDIO

- YAMAHA O 1-V AUDIO CONSOLE, 12 ANALOG INPUTS, 4 DIGITAL INPUTS, 32 CHANNELS, 16 FADERS
- 1 DIGICART

MICROPHONES

- 3 ANNOUNCER HEADSETS
- 4 STUDIO TECHNOLOGIES ANNOUNCE CONSOLES
- 6 LONG SHOTGUN MICROPHONES
- 2 STICK MICROPHONES
- 2 LAVALIER MICROPHONES
- 1 PARABOLIC MIC

RECORD & PLAYBACK

- 1 EVS XT2 6 CHANNEL LSM
- OTHER DEVICES AS NEEDED ON REQUEST

CABLES

- MINI TRIAX: 4 -500' 5 -250'
- DT12 2 -500' 2 -250'
- DT12 FANOUT SETS: 2
- DT12 BREAKOUT BOXES: 1
- TAC-4 ST-ST 1 -1000'
- ASSORTED SINGLE LINE COAX AND XLR CABLES
- 1 SET 75' 4/0 POWER CABLE



XP-1

FLOORPLAN

