

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Product group: Produkt
UFI: 6MWX-AY0P-R9AN-PTSE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

paint Additive

1.3. Details of the supplier of the safety data sheet

Company name: Bergolin GmbH & Co. KG
Street: Sachsenring 1
Place: D-27711 Osterholz-Scharmbeck
Telephone: +49 4795 95899 0
e-mail: info@bergolin.de
Contact person: Gefahrstoffmanagement
e-mail: sdb@bergolin.de
Internet: www.bergolin.de
Responsible Department: Sicherheitsdatenblattverwaltung

1.4. Emergency telephone

+49 4795 95899 0

number:

Only available during office hours. (8-16 CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315
Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Phenol, methyl styrenated
Bis(dodecylthio)dimethylstanane

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 2 of 10

P302+P352 IF ON SKIN: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Solvent-free specialty product

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68512-30-1	Phenol, methyl styrenated			90 - < 95 %
	270-966-8		01-2119555274-38	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H317 H412			
51287-84-4	Bis(dodecylthio)dimethylstanane			5 - < 10 %
	257-111-4		01-2120769343-50	
	Acute Tox. 4, Skin Sens. 1A, Aquatic Chronic 3; H302 H317 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68512-30-1	270-966-8	Phenol, methyl styrenated	90 - < 95 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
51287-84-4	257-111-4	Bis(dodecylthio)dimethylstanane	5 - < 10 %
		oral: LD50 = 1150 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 3 of 10

immediate medical attention.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Health hazard.

Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safe handling: see section 7

Personal protection equipment: see section 8

Clear spills immediately.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Disposal: see section 13

SECTION 7: Handling and storage

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 4 of 10

Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.
Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Use only in well-ventilated areas.

When using do not eat, drink, smoke, sniff.

Take off contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Make available sufficient washing facilities

Further information on handling

Take off contaminated clothing and wash it before reuse.

Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali, Food and feedingstuffs

Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
-	Tin compounds, organic, except Cyhexatin (ISO), (as Sn)	-	0.1		TWA (8 h)	WEL
		-	0.2		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 5 of 10

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
68512-30-1	Phenol, methyl styrenated			
Worker DNEL, long-term		inhalation	systemic	1,4 mg/m³
Worker DNEL, long-term		dermal	systemic	3,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,35 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,7 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,2 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment	Value		
68512-30-1	Phenol, methyl styrenated		
Freshwater	0,014 mg/l		
Marine water	0,0014 mg/l		
Freshwater sediment	1064 mg/kg		
Marine sediment	106 mg/kg		
Micro-organisms in sewage treatment plants (STP)	2,4 mg/l		
Soil	212 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: EN ISO 374 butyl rubber or Viton (necessarily consider the permanence of the material and See information supplied by the manufacturer.)

Breakthrough time (maximum wearing time): not determined

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Thickness of the glove material Breakthrough times and swelling properties of the material must be taken into consideration. Observe the wear time limits as specified by the manufacturer.

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 6 of 10

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	blue
Odour:	characteristic

Test method

Changes in the physical state

Melting point/freezing point:	No data available
-------------------------------	-------------------

Boiling point or initial boiling point and boiling range:	>250 °C
---	---------

Flash point:	> 100 °C DIN 53213
--------------	--------------------

Flammability

Solid/liquid:	No data available
---------------	-------------------

Gas:	No data available
------	-------------------

Auto-ignition temperature:	353 °C
----------------------------	--------

Self-ignition temperature

Solid:	No data available
--------	-------------------

Gas:	No data available
------	-------------------

Decomposition temperature:	No data available
----------------------------	-------------------

pH-Value:	No data available
-----------	-------------------

Flow time:	17
------------	----

(at 20 °C)

Water solubility:	No data available
-------------------	-------------------

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:	No data available
--	-------------------

Vapour pressure:	1 hPa
------------------	-------

(at 20 °C)

Density (at 20 °C):	1,003 g/cm³ DIN 53217
---------------------	-----------------------

Relative vapour density:	No data available
--------------------------	-------------------

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:	No data available
------------------------	-------------------

Oxidizing properties

No data available

Other safety characteristics

Solvent separation test:	<3 % (Land transport (ADR/RID))
--------------------------	---------------------------------

Solid content:	100,00 %
----------------	----------

Evaporation rate:	No data available
-------------------	-------------------

Further Information

*Phenol, methyl styrenated

SECTION 10: Stability and reactivity

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 7 of 10

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

10.5. Incompatible materials

Oxidizing agent, Strong acid, Strong alkali

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68512-30-1	Phenol, methyl styrenated				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
51287-84-4	Bis(dodecylthio)dimethylstanane				
	oral	LD50 1150 mg/kg			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Phenol, methyl styrenated; Bis(dodecylthio)dimethylstanane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Following inhalation:

May cause respiratory irritation. Potential hazards: Liver and kidney damage. Depression of the central nervous system. Symptoms: Headache. Dizziness. Causes drowsiness or dizziness. unconsciousness.

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 8 of 10

After skin contact:

The product is skin resorptive. Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Following eye contact:

Irritating to eyes. (reversible.)

Further information

There are no data available on the mixture itself. Calculation method.

Classification according to Regulation (EC) No 1272/2008 [CLP]

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68512-30-1	Phenol, methyl styrenated					
	Acute fish toxicity	LL50 25,8 mg/l	96 h	Danio rerio		OECD 203
	Acute algae toxicity	ErC50 15 mg/l	72 h	Desmodesmus subspicatus		OECD 201
	Acute crustacea toxicity	EL50 14 mg/l	48 h	Daphnia magna		OECD 202
51287-84-4	Bis(dodecylthio)dimethylstanane					
	Acute algae toxicity	ErC50 270 mg/l	72 h			
	Acute crustacea toxicity	EC50 32 mg/l	48 h			
	Algae toxicity	NOEC 10 mg/l	3 d			

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

No further relevant information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68512-30-1	Phenol, methyl styrenated	>3,6-<6,3
51287-84-4	Bis(dodecylthio)dimethylstanane	13473

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 9 of 10

13.1. Waste treatment methods**Disposal recommendations**

Do not allow to enter into surface water or drains. Remove according to the regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Hazardous waste according to Directive 2008/98/EC (waste framework directive).

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

Recycle according to official regulations.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 20

2010/75/EU (VOC): 0%

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Bis(dodecylthio)dimethylstanane

SECTION 16: Other information

Safety Data Sheet

according to UK REACH Regulation

Steodur-PUR-Beschleuniger 6D972-0000, Blau

Revision date: 07.01.2025

Product code: A1013779

Page 10 of 10

Changes

This data sheet contains changes from the previous version in section(s): 15.

Abbreviations and acronyms

ADR - Accord européen relatif transport des marchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - „Derived No-Effect Level“; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)