



FugeMads

DoP: FM-005-2025

Declaration of Performance

- **Identification code:** FugeMads Design Sealant
- **Batch No.:** See imprint on packaging
- **Intended use:** One component silicone sealant, neutral curing; Sealant for external and internal, not-structural use: facade joints. Type F ext-int CC; glazing applications, type G ext-int CC; sanitary joints, type S, joints in pedestrian walkways, type PW ext-int CC
- **Manufacturer:** FugeMads ApS
Store Valbyvej 99
DK-4000 Roskilde
Denmark
- **System of assessment and verification of constancy** 3 plus 3
- **Notified body** MPA Dortmund NB-No. 0432 performed initial type testing under system 3 and issued the test-report

Declared performance

Essential characteristics

Declared performance

Fire behavior	Class E
Dangerous substances	Assessed (see SDS)
Resistance to flow	≤ 3 mm
Volume loss	≤ 10 %
Elastic recovery	≥ 70 %
Adhesion/cohesion (dry, wet, cold, light)	No failure
Resistance to microorganisms	0 or 1
Durability	No failure

Harmonised Standard: EN 15651:2012 - Parts 1 (F), 2 (G), 3 (S), and 4 (PW)

Declaration

The performance of the product identified above is in conformity with the declared performance listed.

This declaration is issued under the sole responsibility of FugeMads ApS.

Signed for and behalf of the manufacturer

Mads Henriksen
Creative Chief Executive Officer
Roskilde, May 24, 2025