MAINS DISTRIBUTION UNITS

MDU14U | UNSWITCHED WITH INDICATOR



To obtain a quote:

Call: +44 (0)1724 273224

Email: sales@dem-uk.com

- 14 IEC Outlets
- Neutrik PowerCon Input & Loop Connectors
- Front Panel Accessible Fuses, 6 Amp max.

- Green Power Present LED's on Each Output
- Large Rectangular Mains Present Indicator
- 110-230VAC 50Hz



OVERVIEW - Designed as cost effective units, this 1U range includes a 14-way product with loop-through Powercon connector and a 14 output sequential version with 400ms between each output power starting.

FEATURES - The MDU14 is housed in a 19" rack mounted chassis. 14 outputs are individually fused with power present LED's on the front panel. The unit features a loop through connector on the rear to allow daisy chaining of units, provided the circuit is limited to a maximum 16 Amps total at the source. The front panel is made from extruded aluminium, finished in black with a wide clip-on designation strip for clear marking.

Please see page two for electrical specification and dimensions.

All Products in the Low Cost Mains Distribution Unit Range	
Product Code	Description
MDU14	14 Output Mains Distribution Unit with Switch
MDU14S	14 Output Mains Distribution Unit with Sequential Start-up
MDU14U	14 Output Mains Distribution Unit with Indicator

^{**}Colour Options: SG (Storm Grey), DG (Dawn Grey) and BK (Black)

MAINS DISTRIBUTION UNITS LOW COST RANGE - MDU14U



Specification	
Via Neutrik PowerCon	
110-230VAC	
50Hz	
16A	
Total load not to exceed 16A	
6A max HRC fuse per output	
19" rack mount, 1 rack unit high	
Lacing bar at the rear (rack supports	
advised if the cable is not clipped into a	
cable tray at unit height or if the unit is	
vehicle mounted)	

