

		2	3	4	5	6	7
KMF336							
AKA	n/a						
ALTITUDE	2000m						
CURRENT	36A (UL 34A) 40°C						
CLASS	Class I						
DEVICE	rfi filter						
EARTHING	M6x20 stud 4Nm						
ENCLOSURE	aluminium 1.2mm						
ENVIRONMENT	-25/+85/21						
FLAMMABILITY	UL94 V-2 min						
GND BOND	25A 50/60Hz						
HUMIDITY	93% RH non-condensing						
INSULATION	500Vdc ≥3.5MR						
IP RATING	IP20						
LOSS	5.34W/ph						
LEAKAGE	0.9mA operating						
MASS	2.4kg						
MATERIAL	Group IIIa						
MOUNTING	M6 4.5Nm						
MTBF	22yrs (MIL-HDBK-217F)						
OVERLOAD	150% 60s						
OVERVOLTAGE	Category II						
PACKAGING	ASTM D7386						
PCB	FR4 ZPMV2 105°C						
POLLUTION	Degree II						
POTTING	air						
POWER	27.4kW (7.9kW)						
RESIDUAL	292V 5s						
RESISTANCE	4.12mR/ph						
SCCR	5kA (200kA when fused)						
SHOCK	15g 11ms						
SPACING	≥50mm ventilated surfaces						
STYLE	terminal filter						
SUPPLY	3P 50/60Hz						
TERMINAL	screw 1.5-10mm² 1.9Nm 12mm str						
VARISTOR	n/a						
VIBRATION	5-55Hz 350um 55-500Hz 2G						
VOLTAGE	400/480V (520V max)						
WITHSTAND	2900Vdc 60s						
EU/UK	CE/UKCA						
US	uR						
CAN	cUR						
OTHER							



