

# Rx2

## Wireless Audio Receiver | Technical Datasheet

The Rx2 receives wireless audio from compatible Loud of Sweden transmitters using Wireless Local Gateway 2.0 and provides analog and optical outputs for external audio systems.

### KEY FEATURES

- 1.9 GHz DECT wireless audio transmission (WLG 2.0)
- Four selectable volume zones: A, B, C and D
- Analog 3.5 mm line output and optical output
- Pairing with compatible Loud of Sweden transmitters

### TECHNICAL SPECIFICATIONS

|                             |                                    |
|-----------------------------|------------------------------------|
| Wireless technology         | 1.9 GHz DECT / WLG 2.0             |
| Frequency response          | 20 Hz–18 kHz                       |
| Volume zones                | 4 (A / B / C / D)                  |
| Wireless range              | Up to 350 m, outdoor line of sight |
| Analog audio output         | 3.5 mm unbalanced line out         |
| Digital audio output        | 3.5 mm optical (Toslink adapter)   |
| Power supply                | 5 V DC, 1 A via USB-C              |
| Operating power consumption | 1 W                                |
| Weight                      | 50 g                               |
| Dimensions (W × D × H)      | 70 × 65 × 20 mm (excluding feet)   |

### PRODUCT VIEWS

