

Datenblatt

ERGOGRIP SK16**ALLGEMEIN**

Art.Nr:	L-0368-1,8
GTIN:	4030281160410
E-class number:	40-02-01-90
Customs tariff number:	56090000

Standards:	ANSI/ASSP Z359.3-2019, EN 358:2018, MEETS CSA Z259.11-17 CLASS F
Net weight:	1.89 kg
Gross weight:	1.89

Datenblatt

ERGOGRIP SK16

The ERGOGRIP SK16 is a holding rope whose length can be adjusted by means of the runner. A FS 64 ALU carabiner is attached to the rope and a STEEL D TRI carabiner to the runner. (Holding ropes are used for work positioning. The kernmantle ropes used by SKYLOTEC are extremely edge-loadable, abrasion-resistant, remain soft in damp conditions, and have a long service life. The Ergogrip device can be very easily adjusted with one hand).

- Holding rope for workplace positioning
- extremely edge-loadable and abrasion-resistant
- Adjustable length

[VIDEO1](http://www.skylotec.com/media/content/images/PDF/ERGOGRIP_A.mov)

[VIDEO2](http://www.skylotec.com/media/content/images/PDF/ERGOGRIP_B.mov)

MERKMALE

Application areas:	RBA rigging, Wind energy, Telco energy
Fallindicator:	No
Colour:	White, polyethylene_terephthalate, Blue, Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	15.00 kN
Minimum temperature:	-35 °C

MAßE

Lanyard rope diameter:	16.00 mm
------------------------	----------

MATERIAL

Material:	Polyamide, Steel, Aluminium
-----------	-----------------------------