

# DATASHEET

## SUPER STATIC 11.0



### GENERAL

Art.Nr:	R-080-RO-70
GTIN:	4030281029175
E-class number:	40-02-90-06
Customs tariff number:	56075030

Standards:	EN 1891:1998/A
Net weight:	5.51 kg
Gross weight:	5.51 kg

# DATASHEET

## SUPER STATIC 11.0

The semi-static rope SUPER STATIC 11.0 is designed for high loads in working at height as well as for rescue operations. Elongation and jacket slip are reduced to a minimum thanks to innovative technology. The sheath abrasion resistance, on the other hand, is high, making the rope ideal for rope access applications. At the same time the SUPER STATIC 11.0 is supple enough to be used in rescue operations for long abseiling distances. The SUPER STATIC 11.0 is compatible with all ActSafe cable winches.

### FEATURES

Colour:	Red
Number of standard falls:	5
Hand wash:	40 °C
Edge approved:	No
Core ratio:	61.00
Knotability:	1.20
Sheath slippage:	1.00
Maximum lifetime:	10 years
Maximum catch force:	6.00 kN
Minimum tensile strength:	30.00 kN
Minimum strength figure eight knot:	15.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Melting temperature:	215 °C
Shrinkage:	3.00
Rope character:	Static rope
Rope construction:	Kernmantel rope
Rope type industry:	Type A
Static elongation:	4.00
Weight per meter:	71.25 g

### DIMENSIONS

Rope length:	70.00 m
Rope diameter:	11.00 mm

# DATASHEET

## **SUPER STATIC 11.0**

### **MATERIAL**

Material: Polyamide

---