

DATASHEET

SUPER STATIC 11.0



GENERAL

Art.Nr:	R-080-SW-5
GTIN:	4030281013877
E-class number:	40-02-90-06
Customs tariff number:	56075030

Standards:	EN 1891:1998/A
Net weight:	0.57 kg
Gross weight:	0.57 kg

DATASHEET

SUPER STATIC 11.0

The semi-static rope SUPER STATIC 11.0 is designed for high loads in working at height as well as for rescue operations. Elongation and slip are reduced to a minimum thanks to innovative technology. The high sheath abrasion resistance makes the rope ideal for rope access applications. At the same time, the SUPER STATIC 11.0 is supple enough to be used for long abseiling distances during rescue operations. The R-080 version is supplied without sewn terminations. The rope is compatible with ActSafe rope hoists and is available in multiple lengths.

FEATURES

Colour:	Black
Number of standard falls:	5
Hand wash:	40 °C
Edge approved:	No
Core ratio:	61.00
Knotability:	1.20
Sheath slippage:	1.00
Maximum lifetime:	10 years
Maximum catch force:	6.00 kN
Minimum tensile strength:	30.00 kN
Minimum strength figure eight knot:	15.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Melting temperature:	215 °C
Shrinkage:	3.00
Rope character:	Static rope
Rope construction:	Kernmantel rope
Rope type industry:	Type A
Static elongation:	4.00
Weight per meter:	71.25 g

DIMENSIONS

Rope length:	5.00 m
Rope diameter:	11.00 mm

DATASHEET

SUPER STATIC 11.0

MATERIAL

Material: Polyamide
