

DATASHEET

1 SEKURANT® VARIO LINE



GENERAL

Art.Nr: SL-500

E-class number: 40-02-01-90

Standards: ABZ,CEN/TS 16415:
2013,EN 795:2012/C,
UNI 11578:2015

Net weight: 0.00 kg

Gross weight: 0.00 kg

DATASHEET

1 SEKURANT® VARIO LINE

SEKURANT® VARIO LINE is a traversable, 6 mm lifeline system for attaching personal fall protection equipment. Defined deformation in the event of a fall results in minimal force being transferred to the system and the user. It is mainly used on large flat roofs, in production facilities, at sewage treatment plants and silos or in logistics. It does not matter whether the substructure is made of wood, concrete or steel. All components are made of stainless steel and are therefore corrosion-resistant. Thermal bridges are reduced to a minimum thanks to the insulated SEKURANT® VARIO support. The SEKURANT® VARIO LINE system has a building authority approval (abZ) Z-14.9-811 from the German Institute for Building Technology and is also tested and certified in accordance with EN 795:2012 TYPE C, CEN/TS 16415:2013 and UNI 11578:2015.

FEATURES

Colour:	Silver
Type mounting base:	Steel
Mounting type:	Machine screws
Thickness mounting base:	8 mm
Horizontal systems:	Horizontal rope system
Maximum number of persons:	3
Minimum temperature:	-20 °C
Maximum temperature:	80 °C
Rope access technique:	No

DIMENSIONS

Rope length:	200.00 m
Max height:	6 mm
Minimum height:	6 mm

MATERIAL

Material:	Stainless Steel
-----------	-----------------