PRODUCT DATA SHEET



SW600BR Bullet Resistant System





Live Demo Video and Product Page

USES / APPLICATION

Our system utilizes your existing glass and suits retail, distribution centers, K-12 schools, colleges, hospitals, financial institutions, places of worship, corporate HQs, and government buildings. It offers bullet resistance on as thin as 1/4" glass, providing one-way protection for armed guards to stop threats. Resistance varies by threat level. Corporate installers ensure quality, avoiding poor subcontracted work. Existing windows must be inspected for damage and be structurally sound prior to application.

TECHNICAL DATA

PROTECTION LEVEL: EXIGENT PROTECTION

THICKNESS PER LAYER: VARIES

NUMBER OF PLIES: MULTIPLE

BREAK STRENGTH: STARTING AT 1320 PSI

TENSILE STRENGTH: 34,000 PSI

PEEL STRENGTH: 6 PSI

TOTAL SOLAR REJECTION: 20%

IR REJECTION: CAPABLE OF 59%

UV REJECTION: 99%

WEIGHT/SQ FT: 1.6 OUNCES/FT²

7-YEAR LIMITED WARRANTY - EXTENDABLE

LAB TESTING

ANSI Z97.1 - BLDG GLAZE MATERIALS

CPSC 16CFR 1201 - IMPACT TEST

ASTM E 1886 – HURRICANE WIND

GSA EXPLOSIVE TEST - GSA TS01-2003

BMAG LEVEL 1 – BLAST MITIGATION PROTECTION

UL 972/ULC 332 - BURGLARY PROTECTION

NIJ 0108.01 – BULLET RESISTANCE (3RD PARTY LAB)

UL 752 – BULLET RESISTANCE (3RD PARTY LAB)

ASTM F3561 – FORCED ENTRY AFTER SHOOTER ATTACK

