

Technical information

Flooring type		Zenura Elegance LVS
Heterogeneous PVC		Compact flooring
Level of use	EN ISO 10874	EN ISO 10582
Total thickness	EN ISO 24346	23 - 33
Wear layer	EN ISO 24340	2.00 mm
Wear layer PUR treatment		0.50 mm
Fonghi-bacterio static treatment	ISO846-A - ISO22196	Hyperguard+
Total weight/m ²	EN ISO 23997	-
Width	EN ISO 24341	ca. 2,358 g
Standard Length	EN ISO 24341	2-4 m
Weight of standard roll		ca. 25 m
Inflammability	EN 13501	ca. 122-244 kg
Slip resistance	EN 13893	Bfl-S1
Slip restraint	EN 16165 Annex B	DS
Slip classification	EN 13845	R10
Abrasion resistance test	EN 13845	-
RRL Pendulum test (Wet Test)	RRL	-
Residual indentation	EN ISO 24343-1	norm ≤ 0.20 mm
Furniture leg resistance	EN ISO 16581	Pass
Curling	EN ISO 23999	≤ 8 mm
Electrical resistance	EN 1081	1.74 x 10 ⁸ Ohm
Static electrical propensity	EN 1815	≤ 2kV (antistatic)
Dimensional stability	EN ISO 23999	norm ≤ 0.10%
Thermal conductivity	EN 12667	0.147 W/(m.K)
Heat insulation	EN 12667	0.0117 m ² . K/W
Binder quantity in wear layer	EN ISO 10582	Type I
Abrasion group	ISO 660-2	Class T
Indoor air quality		LOW VOC
Acoustic insulation	EN ISO 717-2	ΔLw 8 dB
Castor chair resistance	EN ISO 4918	Pass
Castor type	EN 12529	Type W
Light fastness	ISO 105-B02	≥ 6
Underfloor heating	EN 12524	Suitable ≤27°C
Resistance to chemicals	EN ISO 26987	Very good
Hot welding		Available
Cold welding	Invisiweld	Suitable
Commercial warranty years		12

The warranty covers manufacturing defects and premature wear in the event of normal use.

