

THE CHAMPAGNE CABINET

Manufactured in France 1-temperature cabinet

Small size





Single-temperature cabinet, for serving or ageing champagne

WARRANTY

Technical specifications

Capacity

35 bottles maximum or 22 magnum*

Temperature

- · Default setup temperature: 5°C / 41°F
- ·Temperature setting range from 5°C / 41 to 12/54°F

Design

- · Full Glass door
- · Reversible door (warning on the orientation of the icotype on the handle)
- · Removable Full glass handle
- · Central lock
- · Champagne coloured control panel with glossy finish
- ·White screen display

- · LED screen with touch-sensitive keys
- ·1 ambient light, amber, blue or red (colour to be selected on order)
- · 3 lighting options: permanent, on door opening or off



APRESMAGNUMG


5 bottles

10kg

Sliding presentation shelf ACCHAMPG 8 bottles of champagne 6 magnum of champagne 4.8kg



- · 1 sliding presentation shelf, equipped with a soft close system. 8 removable bottle holders, in brushed stainless steel
- · 2 fixed presentation shelves (standard or magnum bottles). 8 or 5 polished stainless steel bottle holders
- ·Shelves with champagnecoloured lacquer fronts
- · Shiny leather finish to protect bottles and for more comfort of use
- ·1 microfibre cloth
- ·1 erasable felt-tip marker
- ·1 EuroCave keyring



Equipment


Standard shelves

APRESCHAMPG

8 bottles

12kg

Premium pack 3 sliding shelves 35 bottles or 22 magnum



(A la carte) configuration 1 fixed presentation shelf 19 bottles or 9 magnum

Equipment

- · Charcoal filter
- ·Clay ball humidity cassette
- ·2 adjustable feet at the front
- · Condensate drip tray at the back

Regulation

- · Electronic regulation
- · Display of the real temperature inside the cellar
- Display of the humidity when the temperature is set between 9-12°C/ 48-54°F
- · Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- · Automatic defrost

Technologies

Cold production:

Cords:

Heat production:

Heatt release:

Inner material:

Exterior coating material:

Insulation type:

Air fan/Compressor R600a CE/US/UK/JA/AU/CH/C6

Heating element

Automatic/threshold:adjustable

Aluminium

HDF (High Density Fibreboard)

PU foam (59mm)

^{*}Standard champagne format 75 cl- Magnum format 1.5l



General features

	Full Glass door	
Gross weight packaged (kg)	60	
Weight of packaging (kg)	4 (+8kg pallet)	
Dimensions H x W x D (mm)	960x 680 x 720**	
Dimensionsin pack H x W x D	1090x 720 x 760	
Color	Nero - RAL 9005	

^{**}With rear stopper without handle

Energy efficiency and consumption

Cords	230V-50Hz (R600a)	115V-60Hz (R600a)
Type of door	Full Glass	Full Glass
Energy efficiency class	G	G
Annual energy consumption (kWh/year)	128	128
Sound emission (dB(A))	37	37
Sound emission class	C	C
Ambient operating temperatures (C°/°F)	0-30°C / 32-86°F	0-30°C / 32-86°F
Useful volume (litres)	205	

The champagne cabinet, in a few words...

The French way of life

The champagne cabinet is exclusively dedicated to displaying and serving champagne, it is a one-of-a-kind object. Designed to store all shapes and sizes of champagne bottles thanks to its specially designed shelves, this cabinet is a bold homage to the originality of champagne houses and their heritage.







THE CHAMPAGNE CABINET

Manufactured in France

1-temperature cabinet

Large size



Equipment

Standard shelves

APRESCHAMPG

8 bottles

12kg





Single-temperature cabinet, for serving or ageing champagne

Technical specifications

Capacity

91 bottles maximum*

Temperature

- Default setup temperature: 5°C / 41°F
- ·Temperature setting range from 5°C / 41 to 12/54°F

Design

- · Full Glass door
- · Reversible door (warning on the orientation of the icotype on the handle)
- · Removable Full glass handle
- · Central lock
- · Champagne coloured control panel with glossy finish
- ·White screen display

- · LED screen with touch-sensitive keys
- ·1 ambient light, amber, blue or red (colour to be selected on order)
- · 3 lighting options: permanent, on door opening or off



APRESMAGNUMG


5 bottles

10kg

Sliding presentation shelf ACCHAMPG 8 bottles of champagne 6 magnum of champagne 4.8kg



Presentation LUX pack standard 1 fixed presentation shelf sliding shelves 75 hottles



Presentation LUX pack magnum 1 fixed presentation shelf + 6 sliding shelves

Accessories

- · 1 sliding presentation shelf, equipped with a soft close system. 8 removable bottle holders, in brushed stainless steel
- · 2 fixed presentation shelves (standard or magnum bottles). 8 or 5 polished stainless steel bottle holders
- ·Shelves with champagnecoloured lacquer fronts
- · Shiny leather finish to protect bottles and for more comfort of use
- ·1 microfibre cloth
- ·1 erasable felt-tip marker
- ·1 EuroCave keyring

Equipment

- · Charcoal filter
- ·Clay ball humidity cassette
- ·2 adjustable feet at the front
- · Condensate drip tray at the back

Regulation

- · Electronic regulation
- · Display of the real temperature inside the cellar
- Display of the humidity when the temperature is set between 9-12°C/ 48-54°F
- ·Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- · Automatic defrost

10 sliding shelves 91 bottles

Technologies Cold production:

Cords:

Heat production:

Heatt release:

Inner material: **Exterior coating material:**

Insulation type:

Air fan/Compressor R600a CE/US/UK/JA/AU/CH/C6

Heating element

Automatic/threshold:adjustable

Aluminium

HDF (High Density Fibreboard)

PU foam (59mm)

^{*}Standard champagne format





General features

	Full Glass door	
Gross weight packaged (kg)	96	
Weight of reinforced packaging (kg)	13 (+8 kg pallet)	
Dimensions H x W x D (mm)	1825 x 680 x 720**	
Dimensionsin pack H x W x D	1950 x 720 x 760	
Color	Nero - RAL 9005	

^{**}With rear stopper, without handle

Energy efficiency and consumption

Cords	230V-50Hz (R600a)	115V-60Hz (R600a)
Type of door	Full Glass	Full Glass
Energy efficiency class	G	G
Annual energy consumption (kWh/ year)	190	190
Sound emission (dB(A))	37	37
Sound emission class	С	C
Ambient operating temperatures (C°/°F)	0-30°C / 32-86°F	0-30°C / 32-86°F
Useful volume (litres)	46	51

The champagne cabinet, in a few words...

The French way of life

The champagne cabinet is exclusively dedicated to displaying and serving champagne, it is a one-of-a-kind object. Designed to store all shapes and sizes of champagne bottles thanks to its specially designed shelves, this cabinet is a bold homage to the originality of champagne houses and their heritage.



